

Approval body for construction products  
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and  
Laender Governments



## European Technical Assessment

**ETA-07/0142**  
**of 9 December 2016**

English translation prepared by DIBt - Original version in German language

### General Part

Technical Assessment Body issuing the  
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

fischer drop-in anchor EA II

Product family  
to which the construction product belongs

Deformation-controlled expansion anchor for multiple use  
for non-structural applications in concrete

Manufacturer

fischerwerke GmbH & Co. KG  
Klaus-Fischer-Straße 1  
72178 Waldachtal  
DEUTSCHLAND

Manufacturing plant

fischerwerke

This European Technical Assessment  
contains

15 pages including 3 annexes

This European Technical Assessment is  
issued in accordance with Regulation (EU)  
No 305/2011, on the basis of

Guideline for European technical approval of "Metal  
anchors for use in concrete", ETAG 001 Part 6: "Anchors  
for multiple use for non-structural applications",  
April 2013,  
used as European Assessment Document (EAD)  
according to Article 66 Paragraph 3 of Regulation (EU)  
No 305/2011.

This version replaces

ETA-07/0142 issued on 28 July 2016

**European Technical Assessment**

**ETA-07/0142**

English translation prepared by DIBt

**Page 2 of 15 | 9 December 2016**

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

## Specific Part

### 1 Technical description of the product

The fischer drop-in anchor EA II is an anchor made of galvanized or stainless steel which is placed into a drilled hole and anchored by deformation-controlled expansion.

The fixture shall be anchored with a fastening screw or threaded rod according to Annex B 5.

The product description is given in Annex A.

### 2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

### 3 Performance of the product and references to the methods used for its assessment

#### 3.1 Mechanical resistance and stability (BWR 1)

The essential characteristics regarding Mechanical resistance and stability are included under the Basic Works Requirement Safety in use.

#### 3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for Class A1
Resistance to fire	See Annex C 4

#### 3.3 Safety in use (BWR 4)

Essential characteristic	Performance
Characteristic resistance for static and quasi-static loading, displacements	See Annex C 1 to C 3

### 4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with guideline for European technical approval ETAG 001-6, April 2013 used as European Assessment Document (EAD) according to Article 66 Paragraph 3 of Regulation (EU) No 305/2011 the applicable European legal act is: [97/161/EC].

The system to be applied is: 2+

**5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD**


Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 9 December 2016 by Deutsches Institut für Bautechnik


Andreas Kummerow  
p. p. Head of Department

*beglaubigt:*  
Lange


### Multiple use for non-structural applications only



### Intended use in concrete




**Intended use in precast pre-stressed hollow concrete slabs ( $w/e \leq 4,2$ ) with a flange thickness  $\geq 35$  (or 30 mm  $\rightarrow$  see Annex C2) and only for  $h_{ef} = 25$  mm**



fischer drop-in anchor EA II

**Product description**  
Installed condition  
Anchor types

**Annex A 1**




Anchor size EA II	M6x25	M6x30	M8x25	M8x30	M8x40	M10x25	M10x30	M10x40	M12x25	M12x50	M12 D
$h_{ef}$ [mm]	25	30	25	30	40	25	30	40	25	50	50
$\varnothing d_{nom}$ [mm]	8		10			12			15		16
$\varnothing d_{rim}$ [mm]	9,5		11,5			13,5			16,5		17,5
$\varnothing d_1$ [mm]	5		6,5			8,5	8		10		
$l_1$ [mm]	9	14	8	13,5		9	13,5	18,5	10,5	18,5	

#### Distinctive feature




0× groove for:

- EA II M6x30..
- EA II M8x30..
- EA II M10x40..
- EA II M12x50..



1× groove for:

- EA II M6x25..
- EA II M8x25..
- EA II M10x25..
- EA II M12x25..



2× groove for:

- EA II M8x40..
- EA II M10x30..

#### Marking on anchor body


galvanized steel (gvz)		stainless steel (A4)	
with rim	rimless	with rim	rimless
EA II M6x25	EA II M6x25 RL	EA II M6x30 A4	EA II M6x30 RL A4
EA II M6x30	EA II M6x30 RL	EA II M8x30 A4	EA II M8x30 RL A4
EA II M8x25	EA II M8x25 RL	EA II M8x40 A4	EA II M8x40 RL A4
EA II M8x30	EA II M8x30 RL	EA II M10x30 A4	EA II M10x30 RL A4
EA II M8x40	EA II M8x40 RL	EA II M10x40 A4	EA II M10x40 RL A4
EA II M10x25	EA II M10x25 RL	EA II M12x50 A4	EA II M12x50 RL A4
EA II M10x30	EA II M10x30 RL	EA II M12x50 DA4	EA II M12x50 RL DA4
EA II M10x40	EA II M10x40 RL		
EA II M12x25	EA II M12x25 RL		
EA II M12x50	EA II M12x50 RL		
EA II M12x50 D	EA II M12x50 RLD		

fischer drop-in anchor EA II


**Product description**  
Anchor types

**Annex A 2**

Expansion sleeve



Expansion pin



**Table A1: Materials**

Designation	Material	
	galvanised steel ( $\geq 5 \mu\text{m}$ )	stainless steel
Expansion sleeve	EN 10277:2008 or EN 10084:2008 or EN 10111:2008 or EN 10263:2001 or EN 10087:1998 or ASTM A29/A29M	EN 10088:2005
Expansion pin		
Fastening screw or threaded rod	steel, property class 4.6, 5.6, 5.8 or 8.8 according to EN ISO 898-1:2012	property class 50, 70 or 80 according to EN ISO 3506:2009

fischer drop-in anchor EA II

**Product description**  
Material

**Annex A 3**



## Specifications of intended use

### Anchorage subject to:

- Static and quasi-static loads
- Only to be used for multiple use for non-structural application
- Fire exposure: only in concrete C12/15 to C50/60, not prestressed hollow concrete slabs

### Base materials:

- Reinforced or unreinforced normal weight concrete according to EN 206-1:2000
- Strength classes C12/15 to C50/60 according to EN 206-1:2000
- Precast prestressed hollow concrete slabs with  $w/e \leq 4,2$  and strength classes C30/37 to C50/60: M6x25, M8x25, M10x25 and M12x25
- Cracked concrete and non-cracked concrete: all sizes

### Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (zinc coated steel or stainless steel)
- Structures subject to external atmospheric exposure (including industrial and marine environment) and to permanently damp internal condition, if no particular aggressive conditions exist (stainless steel)

Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where de-icing materials are used)

### Design:

- Anchorages are designed under the responsibility of an engineer experienced in anchorages and concrete work
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e. g. position of the anchor relative to reinforcement or to supports, etc.)
- Anchorages under static or quasi-static actions are to be designed in accordance with:
  - ETAG 001, Annex C, design method B and C, Edition August 2010 or
  - CEN/TS 1992-4:2009, design method B
- Fasteners are only to be used for multiple use for non-structural application, according to: ETAG 001 Part 6, Edition August 2010
- Anchorages under fire exposure are designed in accordance with:
  - EOTA Technical Report TR 020, Edition May 2004
  - CEN/TS 1992-4:2009
  - It must be ensured that local spalling of the concrete cover does not occur

### Installation:

- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Create drill hole with hammer drill or with hollow drill and vacuum cleaner
- The anchor may only be used once
- Anchor expansion by impact using the setting tools given in Annex B 4. The anchor is properly set if the stop of the setting tool reaches the expansion sleeve. The manual setting tool with installation control leaves a visible mark on the sleeve, as illustrated in Annex B4 and B 5

fischer drop-in anchor EA II



Intended Use  
Specifications

Annex B 1



**Table B1: Installation parameters for concrete C12/15 to C50/60**

Anchor size			M6		M8			M10			M12		M12D
Nominal drill hole diameter	d <sub>0</sub>	[mm]	8		10			12			15		16
Effective anchorage depth	h <sub>ef</sub>	[mm]	25	30	25	30	40	25	30	40	25	50	50
Maximum installation torque	max. T <sub>inst</sub>	[Nm]	4		8			15			35		
Minimum drill hole depth	h <sub>1</sub>	[mm]	27	32	27	33	43	27	33	43	27	54	54
Minimum screw-in depth	l <sub>s,min</sub>	[mm]	6		8			10			12		
Maximum screw-in depth	l <sub>s,max</sub>	[mm]	14		14			14		17	14	22	
Clearance hole diameter	Ø d <sub>f</sub> ≤	[mm]	7		9			12			14		
h <sub>min</sub> = 80 mm													
Minimum spacing	s <sub>min</sub>	[mm]	30	70	70	110	200	80	200		100	-	-
Minimum edge distance	c <sub>min</sub>	[mm]	60	150	100	150		120	150		130	-	-
h <sub>min</sub> = 100 mm													
Minimum spacing	s <sub>min</sub>	[mm]	30	65	50	70		60	90	150	100	200	
Minimum edge distance	c <sub>min</sub>	[mm]	60	115	100	115		100	160	180	110		
h <sub>min</sub> = 120 mm													
Minimum spacing	s <sub>min</sub>	[mm]	30	65	50	70		60	85	95	100	145	
Minimum edge distance	c <sub>min</sub>	[mm]	60	115	100	115		100	140	150	110	200	



Fastening screw or threaded rod:

- Minimum property class and materials according to table A1
- The length of the fastening screw or threaded rod shall be determined depending on thickness of fixture  $t_{fix}$ , admissible tolerances and maximum screw length  $l_{s,max}$  as well as minimum screw-in depth  $l_{s,min}$ .


fischer drop-in anchor EA II

**Intended Use**  
Installation parameters

**Annex B 2**

**Table B2: Installation parameters for precast pre-stressed hollow concrete slabs**

Anchor size			M6	M8	M10	M12
Nominal drill hole diameter	$d_0$	[mm]	8	10	12	15
Effective anchorage depth	$h_{ef}$	[mm]	25			
Maximum installation torque	max. $T_{inst}$	[Nm]	4	8	15	35
Minimum drill hole depth	$h_1$	[mm]	27			
Minimum screw-in depth	$l_{s,min}$	[mm]	6	8	10	12
Maximum screw-in depth	$l_{s,max}$	[mm]	14			
Clearance hole diameter	$\varnothing d_f$	[mm]	7	9	12	14
Minimum spacing	$s_{min} = s_{cr}$	[mm]	200			
Minimum edge distance	$c_{min} = c_{cr}$	[mm]	150			



Fastening screw or threaded rod:

- Minimum property class and materials according to table A1
- The length of the fastening screw or threaded rod shall be determined depending on thickness of fixture  $t_{fix}$ , admissible tolerances and maximum screw length  $l_{s,max}$  as well as minimum screw-in depth  $l_{s,min}$ .






fischer drop-in anchor EA II

**Intended Use**  
Installation parameters


**Annex B 3**


## Setting & drilling tools

### Setting tools

Setting tools	Marking	Description	Marking on EA II with rim and rimless
	EHS Plus M..x hef	Manual setting tool with hand guard	
	EHS M..x hef	Manual setting tool basic format	
	EMS M..x hef	Machine setting tool with SDS Plus	No marking

### Drilling tools

	EBB ØD x l	Stop drill
Or other usual drillers		



**Table B3: Parameters of setting tools**


Manual setting tool	Machine setting tool	Stop drill	For anchor size	Ø D1	Ø D2	L
EHS M6x25/30	EMS M6x25/30	EBB 8x25 EBB 8x30	EA II M6x25 EA II M6x30	4,8	9,0	17,0
EHS M8x25/30	EMS M8x25/30	EBB 10x25 EBB 10x30	EA II M8x25 EA II M8x30	6,4	11,0	18,0
EHS M8x40	EMS M8x40	EBB 10x40	EA II M8x40			28,0
EHS M10x25/30	EMS M10x25/30	EBB 12x25 EBB 12x30	EA II M10x25 EA II M10x30	7,9	13,0	18,0
EHS M10x40	EMS M10x40	EBB 12x40	EA II M10x40			24,0
EHS M12x25	EMS M12x25	EBB 15x25	EA II M12x25	10,2	16,5	15,2
EHS M12x50	EMS M12x50	EBB 15x50	EA II M12x50	10,2	16,5	30,0
EHS M12x50	EMS M12x50	EBB 16x50	EA II M12x50 D			

fischer drop-in anchor EA II

**Intended Use**  
Setting & Drilling tools

**Annex B 4**

Installation instructions



No.	Description
1	Create drill hole with hammer drill or with hollow drill and vacuum cleaner
2	Clean from drill-dust
3	Set anchor till anchor is flush with surface of concrete
4	Expand the sleeve by driving the pin into the sleeve and control the correct setting
5	Fixation of fixture. Maximum installation torque max. $T_{inst}$ must not be crossed

fischer drop-in anchor EA II

Intended Use  
Installation instructions

Annex B 5

**Table C1: Characteristic values due to design method B according to ETAG 001, Annex C or design method B according to CEN/TS 1992-4: 2009**

Anchor size	Property class screw / rod	M6		M8			M10			M12/M12D	
Effective anchorage depth $h_{ef}$ [mm]		25	30	25	30	40	25	30	40	25	50
<b>All load directions</b>											
Characteristic resistance $F_{RK}^{0(1)}$ [kN]	$\geq A4-50$	-	2	-	3	-	3	5	-	6	
C12/15	$\geq 4.6$	1,5	2	2	3	3	3	5	3	6	
Characteristic resistance $F_{RK}^{0(1)}$ [kN]	$\geq A4-50$	-	3	-	5	-	5	7,5	-	9	
C20/25 to C50/60	$\geq 4.6$	2	3	3	5	4	5	7,5	4	9	
Installation safety factor $\gamma_2 = \gamma_{inst}$		1,0	1,2	1,0	1,2	1,0	1,2	1,0	1,2	1,0	
Characteristic spacing $s_{cr}$ [mm]		75	90	75	90	120	75	90	200	75	300
Characteristic edge distance $c_{cr}$ [mm]		38	45	38	45	60	38	45	100	38	150
<b>Steel failure with lever arm</b>											
Characteristic resistance $M_{RK,s}^{0(2)}$ [Nm]	A4-50	-	8	-	19	-	37	-	66		
Partial safety factor $\gamma_{Ms}$		2,38									
Characteristic resistance $M_{RK,s}^{0(2)}$ [Nm]	A4-70	-	11	-	26	-	52	-	92		
Partial safety factor $\gamma_{Ms}$		1,56									
Characteristic resistance $M_{RK,s}^{0(2)}$ [Nm]	A4-80	-	12	-	30	-	60	-	105		
Partial safety factor $\gamma_{Ms}$		1,33									
Characteristic resistance $M_{RK,s}^{0(2)}$ [Nm]	4.6	6,1	15	30	52						
Partial safety factor $\gamma_{Ms}$		1,67									
Characteristic resistance $M_{RK,s}^{0(2)}$ [Nm]	5.6	7,6	19	37	66						
Partial safety factor $\gamma_{Ms}$		1,67									
Characteristic resistance $M_{RK,s}^{0(2)}$ [Nm]	5.8	7,6	19	37	66						
Partial safety factor $\gamma_{Ms}$		1,25									
Characteristic resistance $M_{RK,s}^{0(2)}$ [Nm]	8.8	12	30	60	105						
Partial safety factor $\gamma_{Ms}$		1,25									

<sup>1)</sup> The anchor is to be used only for multiple use for non-structural applications, the definition of multiple use according to the Member States is given in the informative Annex 1 of ETAG 001 Part 6 (see: [www.eota.eu](http://www.eota.eu))

<sup>2)</sup> Characteristic bending moment  $M_{RK,s}^{0(2)}$  for the equation (5.5) in ETAG 001, Annex C respectively Characteristic bending moment  $M_{RK,s}^{0(2)}$  for the equation (D.5) in CEN/TS 1992-4-1

fischer drop-in anchor EA II

**Performances**

Characteristic values for tension loads in concrete according to design method B

**Annex C 1**




**Table C2: Characteristic values for  $h_{ef} = 25$  mm in precast pre-stressed hollow concrete slabs according to design method C with C30/37 to C50/60**

Anchor size	Property class screw / rod	M6	M8	M10	M12
Effective anchorage depth $h_{ef}$ [mm]		25			
All Load directions		galvanised steel; with rim			
Flange thickness $d_b$ [mm]		$\geq 35$ (or 30 <sup>3)</sup> )			
Characteristic resistance C30/37 to C50/60 $F_{RK}^{1)}$ [kN]		2	3	4	
Installation safety factor $\gamma_2$		1,0			
Characteristic spacing $s_{cr} = s_{min}$ [mm]		200			
Characteristic edge distance $c_{cr} = c_{min}$ [mm]		150			
Steel failure with lever arm					
Characteristic resistance $M^{0}_{RK,s}{}^{2)}$ [Nm]	4.6	6,1	15	30	52
Partial safety factor $\gamma_{Ms}$		1,67			
Characteristic resistance $M^{0}_{RK,s}{}^{2)}$ [Nm]	5.6	7,6	19	37	66
Partial safety factor $\gamma_{Ms}$		1,67			
Characteristic resistance $M^{0}_{RK,s}{}^{2)}$ [Nm]	5.8	7,6	19	37	66
Partial safety factor $\gamma_{Ms}$		1,25			
Characteristic resistance $M^{0}_{RK,s}{}^{2)}$ [Nm]	8.8	12	30	60	105
Partial safety factor $\gamma_{Ms}$		1,25			

<sup>1)</sup> The anchor is to be used only for multiple use for non-structural applications, the definition of multiple use according to the Member States is given in the informative Annex 1 of ETAG 001 Part 6 (see: [www.eota.eu](http://www.eota.eu))

<sup>2)</sup> Characteristic bending moment  $M_{RK,s}^{0}$  for the equation (5.5) in ETAG 001, Annex C

<sup>3)</sup> The anchor may be used in a flange thickness of 30 mm with the same characteristic resistance, but the drill hole is not allowed to cut a cavity (see Annex B5 Point 3).  
The use of the fischer stop drill EBB is recommended



fischer drop-in anchor EA II

#### Performances

Characteristic values for tension loads in hollow core slabs according to design method C

**Annex C 2**

**Table C3: Characteristic resistance under fire exposure<sup>3)</sup> in concrete C20/25 to C50/60 according to design method B, ETAG 001 Annex C or CEN/TS 1992-4: 2009**

fire resistance class	EA II	property class	M6x25	M6x30	M8x25	M8x30	M8x40	M10x25	M10x30	M10x40	M12x25	M12x50/ M12x50D
All load directions												
R 30	Characteristic resistance F <sup>0</sup> <sub>Rk,fi</sub> <sup>1)</sup> [kN] C20/25 to C50/60	steel ≥ 4.6 or ≥ A4-50 <sup>2)</sup>	0,5	0,6	0,9	1,3	0,6	0,9	1,8	0,6	2,3	
R 60			0,5	0,6	0,9	1,5						
R 90			0,4	0,6	0,9	2,0						
R 120			0,3	0,5	0,6	1,3						
R 30 – R 120	Characteristic spacing s <sub>cr,fi</sub> [mm]		100	120	100	120	160	100	120	160	100	200
	Characteristic edge distance c <sub>cr,fi</sub> [mm]		50	115	50	140	140	50	140	160	50	

<sup>1)</sup> In absence of other national regulations, a partial safety factor for the resistance of  $\gamma_{m,fi}=1,0$  under fire stress is recommended

<sup>2)</sup> Not for M..x25

<sup>3)</sup> Not valid for precast pre-stressed hollow core slabs

fischer drop-in anchor EA II

**Performances**  
Characteristic loads for fire resistances

**Annex C 3**