

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments



European Technical Assessment

ETA-16/0584
of 9 December 2016

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

MEYER-PREN ROOF SYSTEM

Product family
to which the construction product belongs

Liquid applied roof waterproofing on the basis of
polyurethane

Manufacturer

Meyer GmbH
Esslinger Straße 3
71334 Waiblingen
DEUTSCHLAND

Manufacturing plant

AB-Polymerchemie GmbH
Tjüchkampstraße 24
26605 Aurich
DEUTSCHLAND

This European Technical Assessment
contains

7 pages including 2 annexes which form an integral part
of this assessment

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

Guideline for European technical approval of "Liquid
applied roof waterproofing kits", ETAG 005 Part 6:
"Specific stipulations for kits based on polyurethane",
used as European Assessment Document (EAD)
according to Article 66 Paragraph 3 of Regulation (EU)
No 305/2011.

This version replaces

ETA-16/0584 issued on 20 July 2016

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific part

1 Technical description of the product

The liquid applied roof waterproofing "MEYER-PREN ROOF SYSTEM" is a kit, which consists of the components:

- primer "MEYER-PREN G 010" on the basis of a two-component epoxy resin on mineral substrates
- liquid applied roof waterproofing "MEYER-PREN S" on the basis of a two-component polyurea for hot spray application (50°C)
- top coat "Meyer-POOL F" on the basis of a two component polyurethane

For an adequate adhesion of waterproofing layer – depending on the type of substrate – a primer is required. In general the primer belonging to the substrate is given in the manufacturer technical documents. In single cases the manufacturer is responsible to give guidance which pretreatment/primer is required.

The minimum layer thickness of the roof waterproofing applied is 3.5 mm.

As an assembled system these components form a homogeneous seamless roof waterproofing. The components and the system build-up of the roof waterproofing "MEYER-PREN ROOF SYSTEM" are given in Annex A.

2 Specification of the intended use in accordance with the applicable EAD

The product is used for the waterproofing of roof surfaces against penetration of atmospheric water.

In the technical file¹ the manufacturer give information concerning the substrates which the product is suitable for and on how these substrates shall be pre-treated.

The levels of use categories are given in Annex A.

The verification and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the product of at least 10 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

The levels of use categories and performances given in Section 3 are only valid if the liquid applied roof waterproofing is used in compliance with the specifications and conditions given in Annex B and the installation instructions of the manufacturer stated in the technical file.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Not applicable

¹ The manufacturer's technical documents comprises all information necessary for the production and the installation of the product as well as for repair of the roof waterproofing made from that and it is deposited with DIBt.

English translation prepared by DIBt

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
External fire performance	See Annex A
Reaction to fire	See Annex A

3.3 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
Water vapour permeability	See Annex A
Watertightness	See Annex A
Release of dangerous substances	The chemical composition of the product has to be in compliance with the composition deposited at the Technical Assessment Body (DIBt). The product does not contain dangerous substances according to EOTA TR 034 (version October 2014).
Resistance to mechanical damage (perforation)	See Annex A, Levels of use categories
Resistance to plant roofs	See Annex A

3.4 Safety and accessibility in use (BWR 4)

Essential characteristic	Performance
Resistance to wind loads	See Annex A
Slipperiness	See Annex A

3.5 Protection against noise (BWR 5)

Not applicable

3.6 Energy economy and heat retention (BWR 6)

Not applicable

3.7 Sustainable use of natural resources (BWR 7)

For the sustainable use of natural resources no performance was investigated for this product.

3.8 General aspects

The verification of durability and serviceability is part of testing the essential characteristics. Durability and serviceability is only ensured if the specifications of intended use according to Annex B and the specifications of the technical file of the manufacturer are kept.

English translation prepared by DIBt

4 Assessment and verification of constancy of performance (AVCP) system applied with reference to its legal base

According to Decision of the Commission of 12 October 1998 (98/599/EC) (OJ L 287 of 24.10.98, p. 30), as amended by Decision of the Commission of 8 January 2001 (2001/596/EC) (OJ L 209 of 02.08.2001, p. 33), the system of assessment and verification of constancy of performance (see Annex V and Article 65 Paragraph 2 to Regulation (EU) No 305/2011) given in the following table applies.

Product	Intended use(s)	Level or class	System
Liquid applied roof waterproofing kits	For uses subject to external fire performance regulations	B _{ROOF} (t1)	3
	For uses subject to reaction to fire	E	3
	All other roof waterproofing uses (all other characteristics)	—	3


5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin 9 December 2016 by Deutsches Institut für Bautechnik

Andreas Kummerow
p. p. Head of Department

beglaubigt:
Gnamou



Applicable to the roof waterproofing "**MEYER-PREN System**"

Minimum layer thickness	3.5 mm	
minimum quantity consumed:	3.0 kg/m ² MEYER-PREN S, 0.4 kg/m ² MEYER-POOL F	
<u>Levels of use categories according to ETAG 005 with relation to:</u>		
Working life:	W2 (10 years)	
Climatic zones	M and S (moderate and severe climatic)	
Resistance to mechanical damage (perforation)	Compressible Substrates: P1 to P3 (from low to normal) Non compressible substrates P1 to P4 (from low to high)	
Roof slope	S1 to S4 (each roof pitch)	
Lowest surface temperature	TL4 (-30 °C)	
Highest surface temperature	TH4 (90 °C)	
Use category related to BWR 3:	I/A 3, S/W 2	
<u>Performance of the product:</u>		
External fire performance	EN 13501-5	B _{Roof} (t ₁)*
Reaction to fire	EN 13501-1	E
Water vapour diffusion resistance factor μ		μ ≈ 810
Watertightness		pass
Statement on dangerous substances		see section 3.3
Resistance to plant roots		no performance assessed
Resistance to wind loads		≥ 50 kPa
Resistance to slipperiness		no performance assessed

*Class **B_{ROOF} (t₁)**

The classification is valid for the following supporting decks:

- all roof pitches > 0°
- any wooden continuous deck with a minimum thickness of 16 mm and gaps not exceeding 0.5 mm
- any non-combustible continuous deck with a minimum thickness of 10 mm
- Any other roof systems for which classification documents for B_{ROOF} (t₁) according EN 13501-5 are available.

MEYER-PREN ROOF SYSTEM

Meyer GmbH

System built-up, levels of use categories and performances of the product

Annex A

Installation

The levels of use categories and the performances of the roof waterproofing can be assumed only, if the installation is carried out according to the installation instructions stated in the technical file of the manufacturer, in particular taking account of the following points:

- installation by appropriately trained personnel,
- installation of only those components which are marked components of the kit,
- installation with the required tools and adjuvants
- precautions during installation,
- inspecting the roof surface for cleanliness and correct preparation, if need be, applying a primer before applying the product,
- inspecting compliance with suitable weather and curing conditions,
- ensuring a thickness of the cured waterproofing of at least 3.5 mm by processing appropriate minimum quantities of material,
- inspections during installation and of the finished product and documentation of the results.

MEYER-PREN ROOF SYSTEM Meyer GmbH	Annex B
Intended use Specifications	