

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments



European Technical Assessment

ETA-16/0204
of 9 December 2016

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

Concrete screw BSZ

Product family
to which the construction product belongs

Concrete screw of sizes 6, 8, 10, 12 and 14 mm for use in
concrete

Manufacturer

MKT
Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
67685 Weilerbach
DEUTSCHLAND

Manufacturing plant

MKT Werk 5, D

This European Technical Assessment
contains

16 pages including 3 annexes which form an integral part
of this assessment

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

Guideline for European technical approval of "Metal
anchor for use in concrete", ETAG 001 Part 3: "Undercut
anchors", April 2013,
used as European Assessment Document (EAD)
according to Article 66 Paragraph 3 of Regulation (EU)
No 305/2011 and European Assessment Document
(EAD) 330011-00-0601.

This version replaces

ETA-16/0204 issued on 14 June 2016

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

English translation prepared by DIBt

Specific Part

1 Technical description of the product

The concrete screw BSZ is an anchor in size 6, 8, 10, 12 and 14 mm made of galvanised steel respectively steel with zinc flake coating, made of stainless or high corrosion resistant steel. The anchor is screwed into a predrilled cylindrical drill hole. The special thread of the anchor cuts an internal thread into the member while setting. The anchorage is characterised by mechanical interlock in the special thread.

Product and product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic values for static and quasi static action	See Annex C 1 and C 2
Characteristic values for seismic category C1	See Annex C 3
Displacements under tension and shear loads	See Annex C 5

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for Class A1
Resistance to fire	See Annex C 4

3.3 Safety in use (BWR 4)

The essential characteristics regarding Safety in use are included under the Basic Works Requirement Mechanical resistance and stability.

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with guideline for European technical approval ETAG 001, April 2013 used as European Assessment Document (EAD) according to Article 66 Paragraph 3 of Regulation (EU) No 305/2011, and European Assessment Document EAD 330011-00-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1

electronic copy of the eta by dibt: eta-16/0204

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable European Assessment Document

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at Deutsches Institut für Bautechnik.

Issued in Berlin on 9 Dezember 2016 by Deutsches Institut für Bautechnik

Andreas Kummerow
p. p. Head of Department

beglaubigt:
Tempel

Product and installation situation


Concrete screw BSZ



BSZ zinc plated



BSZ A4
BSZ HCR



d_0	=	nominal drill hole diameter
h_{nom}	=	nominal embedment depth
h_1	=	depth of the drill hole
h_{min}	=	minimum thickness of member
t_{fix}	=	thickness of fixture
d_f	=	diameter of clearance hole in the fixture

Concrete Screw BSZ

Product description
Product and installation situation

Annex A1

Table A1: Anchor types and description

Anchor type		BSZ -	Description
1		BI	Anchor version with metric connection thread and hexagon socket
2		B	Anchor version with metric connection thread and hexagon drive
3		SU...TX	Anchor version with washer, hexagon head and TORX drive
4		SU	Anchor version with hexagon head and pressed-on washer
5		S	Anchor version with hexagon head
6		SK	Anchor version with countersunk head and TORX drive
7		LK	Anchor version with pan head and TORX drive
8		GLK	Anchor version with large pan head and TORX drive
9		BSK	Anchor version with countersunk head and metric connection thread
10		BS	Anchor version with hexagon drive and metric connection thread
11		M	Anchor version with internal thread and hexagon drive


Concrete Screw BSZ

Product description
Anchor types and description

Annex A2

Table A2: Dimensions

Anchor size			BSZ 6		BSZ 8			BSZ 10			BSZ 12			BSZ 14		
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85	65	85	100	75	100	115
Length of the anchor	$L \leq$	[mm]	500													
Thread	Core diameter	d_k	5,1		7,1			9,1			11,1			13,1		
	Outside diameter	d_s	7,5		10,6			12,6			14,6			16,6		



Marking e.g.: \diamond BSZ 10 100
or TSM 10 100

- \diamond BSZ Trade name (optional with manufacturer identification \diamond)
- or TSM
- 10 Anchor size
- 100 Length of anchor
- A4 additional marking of stainless steel
- HCR additional marking of high corrosion resistant steel

Table A3: Materials

Version	Steel, zinc plated BSZ	Stainless steel BSZ A4	High corrosion resistant steel BSZ HCR
Material	Steel EN 10263-4 galvanized acc. to EN ISO 4042 or zinc flake coating acc. to EN ISO 10683 ($\geq 5\mu\text{m}$)	1.4401, 1.4404, 1.4571, 1.4578	1.4529
Nominal characteristic steel yield strength f_{yk}	560 N/mm ²		
Nominal characteristic steel ultimate strength f_{uk}	700 N/mm ²		
Elongation at fracture A_s	$\leq 8\%$		

Concrete Screw BSZ

Product description
Dimensions, marking and materials

Annex A3

Intended use

Anchorage subject to:

- Static and quasi-static loads,
- Used for anchorages with requirements related to resistance of fire
- Used for anchorages with seismic actions category C1, sizes 8-14 for maximum embedment depth per anchor size

Base materials:

- Reinforced and unreinforced concrete acc. to EN 206-1:2000-12,
- Strength classes C20/25 to C50/60 acc. to EN 206-1:2000-12,
- Cracked and uncracked concrete

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (zinc plated steel, stainless steel or high corrosion resistant steel).
- Structures subject to external atmospheric exposure including industrial and marine environment or exposure to permanently damp internal condition, if no particular aggressive conditions exist (stainless steel or high corrosion resistant steel).
- Structures subject to external atmospheric exposure and to permanently damp internal condition. If other particular aggressive conditions exist (high corrosion resistant steel)

Note: Particular aggressive conditions are e.g. permanent, alternation immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where de-icing materials are used).

Design:

- Anchorages are designed under the responsibility of an engineer experienced in anchorages and concrete work.
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative of reinforcement or to supports, etc.).
- Anchorages under static and quasi-static actions are designed in accordance with:
 - ETAG 001, Annex C, design method A, Edition August 2010 or
 - CEN/TS 1992-4:2009, design method A.
- Anchorages under fire exposure are designed in accordance with:
 - EOTA Technical Report TR 020, Edition May 2004 or
 - CEN/TS 1992-4:2009, Annex D
(It must be ensured that local spalling of the concrete cover does not occur)
- Anchorages under seismic actions are designed in accordance with:
 - EOTA Technical Report TR 045, Edition February 2013
 - Anchorages shall be positioned outside of critical regions (e.g. plastic hinges) of the concrete structure.
 - Fastenings in stand-off installation or with a grout layer are not allowed.
- The design method according to ETAG 001, Annex C also applies for the specified diameter d_f of clearance hole in the fixture in Annex B2, Table B1.
- In CEN/TS 1992-4-1, section 5.2.3.1 the 3. indent will be replaced as follow: only the most unfavorable anchors of an anchor group take up shear loads, if diameter of the clearance hole d_f is larger than given in CEN/TS 1992-4-1, Table 1.
- The condition according to CEN/TS 1992-4-1, Section 5.2.3.3, no. 3) is also fulfilled for the specified diameter d_f of clearance hole in the fixture in Annex B2, Table B1.

Installation:

- Making of drill hole by hammer drilling,
- Anchor installation carried out by appropriately qualified personal and under the supervision of the person responsible for technical matters of the site,
- In case of aborted hole: new drilling at a minimum distance away of twice the depth of aborted hole or smaller distance if the aborted hole is filled with high strength mortar and if under shear or oblique tension load it is not the direction of the load application.
- After installation further turning of the anchor is not possible. The head of the anchor is supported on the fixture and is not damaged.
- The drill hole may be filled with injection mortar MKT BSZ-FM.
- Adjustability according to Annex B4, sizes 8-14, all anchorage depths.

Concrete Screw BSZ

Intended use
Specifications


Annex B1

Table B1: Installation parameters

Anchor size			BSZ 6		BSZ 8			BSZ 10		
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85
Nominal drill hole diameter	d_0	[mm]	6		8			10		
Cutting diameter of drill bit	$d_{cut} \leq$	[mm]	6,4		8,45			10,45		
Depth of drill hole	$h_1 \geq$	[mm]	45	60	55	65	75	65	85	95
Diameter of clearance hole in the fixture	$d_f \leq$	[mm]	8		12			14		
Thickness of fixture	t_{fix}	[mm]	$t_{fix} = L - h_{nom}$							
Max. Installation torque for screws with metric connection thread	$T_{inst} \leq$	[Nm]	10		20			40		
Tangential impact screw driver ¹⁾	$T_{imp,max}$	[Nm]	160		300			400		

Anchor size			BSZ 12			BSZ 14		
Nominal embedment depth	h_{nom}	[mm]	65	85	100	75	100	115
Nominal drill hole diameter	d_0	[mm]	12			14		
Cutting diameter of drill bit	$d_{cut} \leq$	[mm]	12,5			14,5		
Depth of drill hole	$h_1 \geq$	[mm]	75	95	110	85	110	125
Diameter of clearance hole in the fixture	$d_f \leq$	[mm]	16			18		
Thickness of fixture	t_{fix}	[mm]	$t_{fix} = L - h_{nom}$					
Max. Installation torque for screws with metric connection thread	$T_{inst} \leq$	[Nm]	60			80		
Tangential impact screw driver ¹⁾	$T_{imp,max}$	[Nm]	650			650		

¹⁾ Installation with tangential impact screw driver, with maximum power output $T_{imp,max}$ acc. to manufacturers instructions is possible.



Concrete Screw BSZ

Intended use
Installation parameters





Annex B2

Table B2: Minimum thickness of concrete member, minimum spacing and edge distance

Anchor size			BSZ 6		BSZ 8			BSZ 10		
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85
Minimum thickness of member	h_{min}	[mm]	100		100	100	120	100	130	130
Minimum spacing	s_{min}	[mm]	40		40	50		50		
Minimum edge distance	c_{min}	[mm]	40		40	50		50		

Anchor size			BSZ 12			BSZ 14		
Nominal embedment depth	h_{nom}	[mm]	65	85	100	75	100	115
Minimum thickness of member	h_{min}	[mm]	120	130	150	130	150	170
Minimum spacing	s_{min}	[mm]	50		70	50	70	
Minimum edge distance	c_{min}	[mm]	50		70	50	70	

Installation instruction

1		Drill hole perpendicular to concrete surface.
2		Blow out dust or alternatively vacuum clean down to the bottom of the hole.
3		Screw in anchor, e.g. with tangential impact screw driver.
4		After installation, the head of the anchor is supported on the fixture.


Concrete Screw BSZ

Intended use

Minimum thickness of concrete member, minimum spacing and edge distance, installation instruction

Annex B3

Installation instruction for adjustment M8-M14



- The anchor may be adjusted at most two times while the anchor may be turned back at most 10 mm.
- The total allowed thickness of shims added during the adjustment process is 10 mm.
- The required setting depth h_{nom} must be maintained after the adjustment. ($h_{nom} = L - t_{fix}$).

Concrete Screw BSZ

Intended use
Installation instruction for adjustment

Annex B4

Table C1: Characteristic values for tension loads

Anchor size			BSZ 6		BSZ 8			BSZ 10			
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85	
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0								
Steel failure											
Characteristic load	$N_{Rk,s}$	[kN]	14		27			45			
Pull-out failure											
Characteristic tension load in concrete C20/25	cracked	$N_{Rk,p}$	[kN]	2	4	5	9	12	9	1)	
	uncracked	$N_{Rk,p}$	[kN]	4	9	7,5	12	16	12	20	25
Increasing factor for $N_{Rk,p}$ for strength classes > C20/25	ψ_C	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$								
Concrete cone failure											
Effective anchorage depth	h_{ef}	[mm]	31	44	35	43	52	43	60	68	
Spacing (Edge distance)	$s_{cr,N}$ ($c_{cr,N}$)	[mm]	3 h_{ef} (1,5 h_{ef})								
Factor for concrete (acc. to CEN/TS 1992-4)	cracked	k_{cr}	7,2								
	uncracked	k_{ucr}	10,1								
Splitting											
Spacing	$s_{cr,sp}$	[mm]	120	160	120	140	150	140	180	210	
Edge distance	$c_{cr,sp}$	[mm]	60	80	60	70	75	70	90	105	
Anchor size			BSZ 12				BSZ 14				
Nominal embedment depth	h_{nom}	[mm]	65	85	100	75	100	115			
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0								
Steel failure											
Characteristic load	$N_{Rk,s}$	[kN]	67				94				
Pull-out failure											
Characteristic tension load in concrete C20/25	cracked	$N_{Rk,p}$	[kN]	12	1)			1)			
	uncracked	$N_{Rk,p}$	[kN]	16							
Increasing factor for $N_{Rk,p}$ for strength classes > C20/25	ψ_C	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$								
Concrete cone failure											
Effective anchorage depth	h_{ef}	[mm]	50	67	80	58	79	92			
Spacing (Edge distance)	$s_{cr,N}$ ($c_{cr,N}$)	[mm]	3 h_{ef} (1,5 h_{ef})								
Factor for concrete (acc. to CEN/TS 1992-4)	cracked	k_{cr}	7,2								
	uncracked	k_{ucr}	10,1								
Splitting											
Spacing	$s_{cr,sp}$	[mm]	150	210	240	180	240	280			
Edge distance	$c_{cr,sp}$	[mm]	75	105	120	90	120	140			

1) Pull-out is not decisive

Concrete Screw BSZ

Performance
Characteristic values for tension loads

Annex C1

Table C2: Characteristic values for **shear loads**

Anchor size			BSZ 6		BSZ 8			BSZ 10		
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0							
Steel failure without lever arm										
Characteristic load	$V_{Rk,s}$	[kN]	7	13,5			17	22,5		34
Factor of ductility acc. to CEN/TS 1992-4	k_2	[-]	0,8							
Steel failure with lever arm										
Characteristic bending moment	$M^0_{Rk,s}$	[Nm]	10,9		26			56		
Concrete pry-out failure										
Factor k acc. to ETAG 001, Annex C or k_3 acc. to CEN/TS 1992-4	$k_{(3)}$	[-]	1,0		1,0			1,0		2,0
Concrete edge failure										
Effective length of anchor	$l_f = h_{ef}$	[mm]	31	44	35	43	52	43	60	68
Outside diameter of anchor	d_{nom}	[mm]	6		8			10		
Anchor size			BSZ 12			BSZ 14				
Nominal embedment depth	h_{nom}	[mm]	65	85	100	75	100	115		
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0							
Steel failure without lever arm										
Characteristic load	$V_{Rk,s}$	[kN]	33,5	42			56			
Factor of ductility acc. to CEN/TS 1992-4	k_2	[-]	0,8							
Steel failure with lever arm										
Characteristic bending moment	$M^0_{Rk,s}$	[Nm]	113			185				
Concrete pry-out failure										
Factor k acc. to ETAG 001, Annex C or k_3 acc. to CEN/TS 1992-4	$k_{(3)}$	[-]	1,0	2,0			1,0	2,0		
Concrete edge failure										
Effective length of anchor	$l_f = h_{ef}$	[mm]	50	67	80	58	79	92		
Outside diameter of anchor	d_{nom}	[mm]	12			14				
Concrete Screw BSZ										Annex C2
Performance Characteristic values for shear loads										

Table C3: Characteristic resistance for **seismic loading**, Category **C1**

Anchor size		BSZ 8	BSZ 10	BSZ 12	BSZ 14
Nominal embedment depth	h_{nom} [mm]	65	85	100	115
Installation safety factor	γ_2 [-]	1,0			
Tension load					
Steel failure					
Characteristic resistance	$N_{Rk,s,seis}$ [kN]	27	45	67	94
Pull-out failure					
Characteristic resistance in concrete C20/25 to C50/60	$N_{Rk,p,seis}$ [kN]	12	1)		
Concrete cone failure					
Effective anchorage depth	h_{ef} [mm]	52	68	80	92
Spacing	$s_{cr,N}$ [mm]	3 h_{ef}			
Edge distance	$c_{cr,N}$ [mm]	1,5 h_{ef}			
Shear load					
Steel failure without lever arm					
Characteristic resistance	$V_{Rk,s,seis}$ [kN]	8,5	15,3	21,0	22,4
Concrete pry-out failure					
Factor k acc. to ETAG 001, Annex C	k [-]	1,0	2,0		
Concrete edge failure					
Effective length of anchor	$l_f = h_{ef}$ [mm]	52	68	80	92
Outside diameter of anchor	d_{nom} [mm]	8	10	12	14

¹⁾ Pull-out is not decisive

Concrete Screw BSZ

Performance
Characteristic values for **seismic loading**, Category **C1**

Annex C3

Table C4: Characteristic values under fire exposure

Anchor size			BSZ 6		BSZ 8			BSZ 10			BSZ 12			BSZ 14			
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85	65	85	100	75	100	115	
Steel failure (tension and shear load)																	
Characteristic resistance	R30	$N_{RK,s,fi}$ = $V_{RK,s,fi}$	[kN]	0,9		2,4			4,4			7,3			10,3		
	R60			0,8		1,7			3,3			5,8			8,2		
	R90			0,6		1,1			2,3			4,2			5,9		
	R120			0,4		0,7			1,7			3,4			4,8		
Steel failure with lever arm																	
Characteristic bending moment	R30	$M^0_{RK,s,fi}$	[Nm]	0,7		2,4			5,9			12,3			20,4		
	R60			0,6		1,8			4,5			9,7			15,9		
	R90			0,5		1,2			3,0			7,0			11,6		
	R120			0,3		0,9			2,3			5,7			9,4		
Spacing	$s_{cr,fi}$	[mm]	4 h_{ef}														
Edge distance	$c_{cr,fi}$	[mm]	2 h_{ef}														

The characteristic resistance for pull-out, concrete cone failure, concrete pry-out and concrete edge failure shall be calculated according to TR 020 / CEN/TS 1992-4. If no value for $N_{RK,p}$ is given, in Eq. 2.4 and Eq. 2.5, TR 020 (or Eq. D1 and D.2, CEN/TS 1992-4) $N_{RK,p}$ must be replaced by the value of $N^0_{RK,c}$.

Concrete Screw BSZ

Performance
Characteristic values under fire exposure

Annex C4

Table C5: Displacements under tension load

Anchor size			BSZ 6		BSZ 8			BSZ 10			
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85	
Cracked concrete	Tension load	N [kN]	0,95	1,9	2,4	4,3	5,7	4,3	7,9	9,6	
	Displacement	δ_{N0}	[mm]	0,3	0,6	0,6	0,7	0,8	0,6	0,5	0,9
		$\delta_{N\infty}$	[mm]	0,4	0,4	0,6	1,0	0,9	0,4	1,2	1,2
Uncracked concrete	Tension load	N [kN]	1,9	4,3	3,6	5,7	7,6	5,7	9,5	11,9	
	Displacement	δ_{N0}	[mm]	0,4	0,6	0,7	0,9	0,5	0,7	1,1	1,0
		$\delta_{N\infty}$	[mm]	0,4	0,4	0,6	1,0	0,9	0,4	1,2	1,2

Anchor size			BSZ 12			BSZ 14			
Nominal embedment depth	h_{nom}	[mm]	65	85	100	75	100	115	
Cracked concrete	Tension load	N [kN]	5,7	9,4	12,3	7,6	12,0	15,1	
	Displacement	δ_{N0}	[mm]	0,9	0,5	1,0	0,5	0,8	0,7
		$\delta_{N\infty}$	[mm]	1,0	1,2	1,2	0,9	1,2	1,0
Uncracked concrete	Tension load	N [kN]	7,6	13,2	17,2	10,6	16,9	21,2	
	Displacement	δ_{N0}	[mm]	1,0	1,1	1,2	0,9	1,2	0,8
		$\delta_{N\infty}$	[mm]	1,0	1,2	1,2	0,9	1,2	1,0

Table C6: Displacements under shear load

Anchor size			BSZ 6		BSZ 8			BSZ 10			BSZ 12			BSZ 14		
Nominal embedment depth	h_{nom}	[mm]	40	55	45	55	65	55	75	85	65	85	100	75	100	115
Shear load	V	[kN]	3,3		8,6			16,2			20,0			30,5		
Displacement	δ_{V0}	[mm]	1,55		2,7			2,7			4,0			3,1		
	$\delta_{V\infty}$	[mm]	3,1		4,1			4,3			6,0			4,7		

Concrete Screw BSZ

Performance
Displacements

Annex C5