

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments



European Technical Assessment

ETA-08/0250
of 9 February 2017

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

Kaubiflex FA-System

Product family
to which the construction product belongs

Liquid applied watertight covering for wet rooms with
wearing surface

Manufacturer

Kaubit AG
Industriestraße 1
49413 Dinklage
DEUTSCHLAND

Manufacturing plant

Kaubit AG
Industriestraße 1
49413 Dinklage
DEUTSCHLAND

This European Technical Assessment
contains

11 pages including 5 annexes which form an integral part
of this assessment

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

Guideline for European technical approval of "Watertight
Covering Kits for Wet Room Floors and/or Walls",
ETAG 022 Part 1: "Liquid Applied Coverings with or
without Wearing Surface",
used as European Assessment Document (EAD)
according to Article 66 Paragraph 3 of Regulation (EU)
No 305/2011.

This version replaces

ETA-08/0250 issued on 20 March 2013

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific part

1 Technical description of the product

The watertight covering "Kaubiflex FA-System" is a kit. It consists of the following components:

- Primer "Kaubit primer UKD 200" on the basis of styrol-butadien or "Kaubit Primer DS 2" on the basis of a polymer dispersion
- one-component liquid waterproofing membrane "Kaubiflex FA Sealing Compound" on the basis of styrol-butadien
- sealing tape Type "NG", "NV", "NVV", "PEVV" or "PEVV perforated"
- sealing ingoing and outgoing corners Type "NG", "NV", "NVV", "PEVV" or "PEVV perforated"
- sealing sleeves for walls "NG", "NV", "NVV", "NVV perforated"
- sealing sleeves for floor gullies "NG", "NV", "NVV", "NVV perforated" or "Butyl"
- adhesive "Kaubit FM Flex" according to EN 12004¹

The kit is intended to be used under a wearing surface, e.g. tiles. The wearing surface and the jointing material are not part of the kit, but are considered during the assessment of the intended use of the product.

Annex A1 shows the system build-up and annex A2 to A4 shows the components for sealing details.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The intended use of the watertight covering under a wearing surface is to create a floor and wall watertight covering for indoor wet areas at possible operating temperature of 5 °C till 40 °C.

The following uses are intended:

- Floor and/or wall surfaces with only occasional direct exposure to water, e. g. at a good distance from shower or bathtub;
- Floor and/or wall in shower areas or around bathtubs used for a few showers daily, e. g. in ordinary dwellings, multifamily houses and hotels;
- Floor and/or wall surfaces with exposure to water more frequent or of longer duration than normally anticipated in dwellings, e. g. public wet rooms, schools and sport facilities.

The watertight membrane is intended to be used on flexible substrate e. g. plywood, chipboard, gypsum, anhydrite or similar material vulnerable to water and on rigid substrates e. g. masonry or concrete.

¹ EN 12004:2014-02 Adhesives for tiles - Requirements, evaluation of conformity, classification and designation

English translation prepared by DIBt

The product should be used in connection with the following types of gullies:

Stainless steel or plastics – type PP or PE – with flange for attaching of collar/membrane or with clamping ring and collar.

The gullies are not part of the kit. It is up to the responsibility of the user to use suitable products of the given types.

The performances given in Section 3 are only valid if the watertight covering kit is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the watertight covering kit of at least 25 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Not applicable

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	See Annex A1

3.3 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
contain dangerous substances	
Component: Tile adhesive (CE-marked)	According to EN 12004
Other components: Carcinogenic substances, classified as EU-Kat. Carc. 1A/1B (H350, H350i) and mutagenic substances, classified as EU-Kat. Muta. 1A/1B (H340), according to the regulation (EG) Nr. 1272/2008.	No activ dangerous substances in these components ²
release dangerous substances	
release scenario concerning BWR 3: IA2, IA3 (according to EOTA TR 034)	npa
Vapour permeability	See Annex A1, declared value
Watertightness	See Annex A1
Crack bridging ability	See Annex A1, category
Bond strength	See Annex A1, category
Scratching resistance	See Annex A1, declared value
Joint bridging ability	See Annex A1, category
Watertightness around penetrations	See Annex A1, category

² The evaluation based on the manufactured' s declarations.

English translation prepared by DIBt

3.4 Safety and accessibility (BWR 4)

Essential characteristic	Performance
Slipperiness	See Annex A1, declared value

3.5 Protection against noise (BWR 5)

Not applicable

3.6 Energy economy and heat retention (BWR 6)

Not applicable

3.7 Sustainable use of natural resources (BWR 7)

For the sustainable use of natural resources no performance was investigated for this product.

3.8 General aspects

The verification of durability and serviceability is part of testing the essential characteristics and by additional tests on the kit respectively on the components:

Essential characteristic	Performance
Resistance to temperature	See Annex A1, category
Resistance to water	See Annex A1, category
Resistance to alkalinity	See Annex A1, category
Resistance to mechanical wear	See Annex A1, declared value
Cleanability	See Annex A1, declared value
Reparability	See Annex A1, statement of the manufacturer
Thickness	See Annex A1, declared value
Applicability	See Annex A1, declaration

The verification of durability and serviceability is only ensured if the specifications of intended use according to Annex B1 and the specifications of the technical file of the manufacturer are kept.

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

According to Decision of the Commission of 12 September 2003 (2003/655/EC) (OJ L 231 of 17.09.2003, p. 12) the system of assessment and verification of constancy of performance (see Annex V and Article 65 Paragraph 2 to Regulation (EU) No 305/2011) given in the following table applies.

Product	Intended use(s)	Level or class	System
Watertight covering kits for wetroom floors and walls	For building works	-	2+
	For uses subject to regulation on reaction to fire	E	3

English translation prepared by DIBt


5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 9 February 2017 by Deutsches Institut für Bautechnik

Uwe Bender
Head of Department

beglaubigt:
Gnamou



Minimum layer thickness of the waterproofing sheet 0.5 mm

Level of use categories according to ETAG 022 with relation to:

Use category related to BWR 3	IA2, S/W3
Crack bridging ability	category 1: 0.4 mm
Bond strength	category 2: ≥ 0.5 MPa
Joint bridging ability	category 2: watertight
Water tightness around penetrations	category 2: watertight
Resistance to water	category 2: ≥ 0.5 MPa
Resistance to alkalinity	category 2: ≥ 0.5 MPa

Performance of the product:

Working life	25 years
Reaction to fire acc. to EN 13501-1	class E
Statement on dangerous substance	see section 3.3
Water vapour diffusion resistance factor	
Kaubit primer UKD 200 with Kaubiflex FA sealing compound (1000 g/m ²) 23 °C – 50/93 % r.h.	$s_d = 2,3$ m
Kaubit Primer DS 2 (460 g/m ²) with Kaubiflex FA sealing compound (1000 g/m ²) 23 °C – 75/100 % r.h.	$s_d = 79$ m
Water tightness acc. to EN 13967	watertight
Scratch resistance	not relevant acc. ETAG 022-1
Resistance to mechanical wear	not relevant acc. ETAG 022-1
Cleanability	not relevant acc. ETAG 022-1
Reparability	reparable
Slipperiness	npa
Applicability	applicable
Resistance to temperature	category 2: $\geq 0,5$ MPa

Kaubiflex FA-System
Kaubit AG

System built-up, levels of use categories and performances of the product

Annex A1

Sealing tape:



Type "NG" width 120 mm
Type "NV" width 120 mm




Type "NVV" width 120 mm




Type "PEVV" width 120 mm
with and without perforation

Kaubiflex FA-System Kaubit AG	Annex A2
Details and components	


Ingoing/outgoing corners:




Type "NG"
Type "NV"
leg length 100 or 140 mm



Type "NG"
Type "NV"
leg length 75 or 140 mm



Type "NVV"
leg length 100 or 140 mm



Type "NVV"
leg length 75 or 140 mm



Type "PEVV" leg length 120 mm
with and without perforation



Type "PEVV" leg length 105 mm
with and without perforation



electronic copy of the eta by dibt: eta-08/0250

Kaubiflex FA-System
Kaubit AG

Details and Components

Annex A3



Sealing sleeves for walls:



Type NG" 100 x 100 mm, 150 x 150 mm, 200 x 200 mm
Type NV" 100 x 100 mm, 150 x 150 mm, 200 x 200 mm

Type NVV" 100 x 100 mm, 150 x 150 mm, 200 x 200 mm with and without perforation

Sealing sleeves for floors:



Type "NG" 350 x 350 mm, 400 x 400 mm
Type "NV" 350 x 350 mm, 400 x 400 mm

Type "NVV" 350 x 350 mm
with and without perforation



Type "Butyl" 370 x 370 mm

electronic copy of the eta by dibt: eta-08/0250

Kaubiflex FA-System
Kaubit AG

Details and components

Annex A4

Installation

The levels of use categories and the performance of the waterproofing kit can be assumed only, if the installation is carried out according to the installation instructions stated in the technical file of the manufacturer, in particular taking account of the following points:

- installation by appropriately trained personnel,
- installation of only those components which are specified components of the kit,
- installation with the required tools and adjuvant,
- precautions during installation,
- inspecting the substrate surface for cleanliness and correct treatment,
- inspecting during installation and of the finished watertight membrane and documentation of the results.

Kaubiflex FA-System Kaubit AG	Annex B
Intended use Specifications	