

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments



European Technical Assessment

ETA-10/0251
of 17 December 2019

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

VIASAN

Product family
to which the construction product belongs

Liquid applied roof waterproofing system on the basis of
polyurethan

Manufacturer

VIA DACHTEILE GmbH & Co. KG
Bramfelder Chaussee 100
22177 Hamburg
DEUTSCHLAND

Manufacturing plant

VIA DACHTEILE GmbH & Co. KG
Hauptlager

This European Technical Assessment
contains

7 pages including 3 annexes which form an integral part
of this assessment

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

ETAG 005 Part 6: "Specific stipulations for kits based on
polyurethane",
used as EAD according to Article 66 Paragraph 3 of
Regulation (EU) No 305/2011.

This version replaces

ETA-10/0251 issued on 18 September 2017

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific part

1 Technical description of the product

The liquid applied roof waterproofing system "VIASAN" is a kit. The kit consists of the components:

- supporting layer: roof waterproofing sheet "VIA-UP 3" , clutched on upper side with polyester fleece
- cover layer: liquid applied roof waterproofing on the basis of a two component polyurethane "QuiTex DA" or "Quitex B"
- stripes of polyester fleece for reinforcement

For an adequate adhesion of the waterproofing layer – depending on the type of substrate – a primer on the basis of bitumen is required.

The minimum layer thickness of the roof waterproofing system "VIASAN" applied is 3.5 mm.

As an assembled system these components form a homogeneous seamless roof waterproofing.

The components and the system build-up of the roof waterproofing "VIASAN" are given in Annex A1.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The liquid applied roof waterproofing system is used for the waterproofing of roof surfaces against penetration of atmospheric water.

The roof waterproofing is suitable for non-compressible substrates (e.g. steel, concrete) and compressible substrates (e.g. insulation boards).

In the technical documents¹ the manufacturer give information concerning the substrates which the roof waterproofing is suitable for and on how these substrates shall be pre-treated.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the roof waterproofing of at least 25 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

The levels of use categories are given in Annex A1.

The levels of use categories and performances given in Section 3 are only valid if the liquid applied roof waterproofing is used in compliance with the specifications and conditions given in Annex B and the installation instructions stated in the manufacturer's technical documents.

3 Performance of the product and references to the methods used for its assessment

3.1 Safety in case of fire (BWR 2)

Essential characteristic	Performance
External fire performance	See Annex A2
Reaction to fire	See Annex A2

¹ The manufacturer's technical documents comprises all information necessary for the production and the installation of the product as well as for repair of the roof waterproofing made from that and it is deposited with DIBt.

3.2 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
Water vapour permeability	See Annex A2
Watertightness	See Annex A2
Release of dangerous substances	No performance assessed
Resistance to mechanical damage (perforation)	See Annex A1
Resistance to plant roots	See Annex A2

3.3 Safety and accessibility in use (BWR 4)

Essential characteristic	Performance
Resistance to wind loads	See Annex A2
Slipperiness	See Annex A2

3.4 General aspects

The verification of durability and serviceability is part of testing the essential characteristics. Durability and serviceability are only ensured if the specifications of intended use according to Annex B and the specifications of the technical documents of the manufacturer are kept.

4 Assessment and verification of constancy of performance (AVCP) system applied with reference to its legal base

In accordance with ETAG 005 used as EAD, the applicable European legal act is: 98/599/EC

The system to be applied is: 3

In addition, with regard to e.g. reaction to fire for products covered by this ETAG the applicable European legal act is: 2001/596/EC

The system to be applied is: 3

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD


Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 17 December 2019 by Deutsches Institut für Bautechnik

BD Dipl.-Ing. Andreas Kummerow
Head of Department

beglaubigt:
Gnamou

System build-up of the roof waterproofing system "VIASAN"



Components:

- 1 Sheet "VIA-UP 3" clutched with polyester fleece with a nominal weight of 180 g/m²
- 2 Stripes of polyester fleece
- 3 Liquid synthetic material "QuiTex DA" or "QuiTex B" (0,45 g/m²) over joint
- 4 Liquid synthetic material "QuiTex DA" or "QuiTex B" (1,5 g/m²)

Applicable for roof waterproofing system "VIASAN":

With the liquid waterproofing	QuiTex DA	QuiTex B
Minimum layer thickness:		
- sheet	3.0 mm	
- liquid synthetic material	0.5 mm	
- system	3.5 mm	
minimum quantity consumed:	1.8 kg/m ²	
<u>Levels of use categories according to ETAG 005 with relation to:</u>		
Working life:	W3 (25 years)	
Klimazonen	M (moderate)	
Resistance to mechanical damage (perforation) (compressible and non-compressible substrates)	P1 to P3 (from low to normal)	
Roof slope:	S1 to S4 (all slopes)	
Lowest surface temperature:	TL3 (-20° C)	
Highest surface temperature:	TH4 (90° C)	
Use category related to BWR 3:	S/W 3	

Roof waterproofing system "VIASAN"
VIA-Dachteile GmbH & Co. KG

System built-up and levels of use categories of the product

Annex A1

<u>Performance of the product:</u>		
External fire performance	EN 13501-5	$B_{ROOF} (t_1)^*$
Reaction to fire	EN 13501-1	E
Water vapour diffusion resistance factor μ		$\mu \geq 240000$ (at 0% to 75 % r.F)
Watertightness		watertight
Statement on dangerous substances		see section 3.2
Resistance to plant roots		no performance assessed
Characteristic wind uplift resistance		≥ 2500 Pa
Resistance to wind loads		≥ 50 kPa for tear resistant substrates
Resistance to slipperiness		no performance assessed

Class $B_{ROOF} (t_1)$

The classification is valid for the following supporting decks:

- for roof pitches $< 20^\circ$
- any wooden continuous deck with a minimum thickness of 16 mm and with gaps not exceeding 0.5 mm
- any non-combustible continuous deck with a minimum thickness of 10 mm
- with EPS DAA (EN 13163) clutched with GVK100 with a thickness of 100 mm

Any other roof system for which classification documents for $B_{ROOF} (t_1)$ according to EN 13501-5 are available.

Roof waterproofing system "VIASAN"

VIA-Dachteile GmbH & Co. KG

Classifications of the product

Annex A2

Installation

The levels of use categories and the performances of the roof waterproofing system can be assumed only, if the installation is carried out according to the installation instructions stated in the technical file of the manufacturer, in particular taking account of the following points:

- installation by appropriately trained personnel
- installation of only those components which are marked components of the kit
- installation with the required tools and adjuvants
- precautions during installation
- inspecting the roof surface for cleanliness and correct preparation, if need be, applying a primer before applying the product
- inspecting compliance with suitable weather and curing conditions
- ensuring a thickness of the waterproofing of at least 3.5 mm by processing appropriate minimum quantities of material
- inspections during installation and of the finished product and documentation of the results

Electronic copy of the ETA by DIBt: ETA-10/0251

Roof waterproofing system "VIASAN" VIA-Dachteile GmbH & Co. KG	Annex B
Intended use Specifications	