

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments



European Technical Assessment

ETA-19/0363
of 7 August 2019

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

"Rygol Perimeterdämmplatte 035 PERI-BLOCK 3m"

Product family
to which the construction product belongs

Expanded polystyrene (EPS) foam boards as thermal
insulation outside the waterproofing

Manufacturer

RYGOL DÄMMSTOFFE
Werner Rygol GmbH & Co. KG
Kelheimer Straße 37
93351 Painten
DEUTSCHLAND

Manufacturing plant

RYGOL DÄMMSTOFFE
Werner Rygol GmbH & Co. KG
Kelheimer Straße 37
93351 Painten
GERMANY

This European Technical Assessment
contains

6 pages which form an integral part of this assessment

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

EAD 040773-00-1201

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific Part

1 Technical description of the product

This European Technical Assessment applies to the thermal insulation boards of expanded polystyrene (EPS) with the designation:

"Rygol Perimeterdämmplatte 035 PERI-BLOCK 3m"

This European Technical Assessment applies to thermal insulation boards with a nominal thickness from 80 mm to 400 mm.

From a nominal thickness of 200 mm the thermal insulation boards have a special edge treatment (shiplap, depth ≥ 15 mm).

By a nominal thickness < 200 mm the thermal insulation boards can have a special edge treatment (shiplap, depth ≥ 15 mm).

The thermal insulation boards do not contain Hexabromocyclododecane (HBCD).

The European Technical Assessment has been issued for the product on the basis of agreed data/information, deposited with Deutsches Institut für Bautechnik, which identifies the product that has been assessed. The European Technical Assessment applies only to the product corresponding to this agreed data/information.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The thermal insulation boards are intended to be used as external horizontal and vertical thermal insulation of in-ground constructions outside the waterproofing (non-structural application) not constantly exposed to groundwater or to long-term backwater.

The performance according to section 3 only applies if the thermal insulation boards are installed according to the manufacturer's installation instructions and if they are protected from precipitation, wetting or weathering during transport and storage before installation.

Concerning the application of the thermal insulation boards, also the respective national regulations shall be observed.

Where the thermal insulation boards are fixed by using adhesives, only such adhesives shall be used, which are suitable for this purpose. The assessment of these fixings is not subject of this European Technical Assessment.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the thermal insulation boards of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

For sampling, conditioning and testing the provisions of the EAD No 040773-00-1201 apply.

3.1 Mechanical resistance and stability (BWR 1)

Not applicable

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire test acc. to EN ISO 11925-2:2010	Class E acc. to EN 13501-1:2007 + A1:2009

3.3 Hygiene, health and environment (BWR 3)

Not applicable

3.4 Safer and accessibility in use (BWR 4)

Not applicable

3.5 Protection against noise (BWR 5)

Not applicable

3.6 Energy economy and heat retention (BWR 6)

Essential characteristic	Performance
Thermal conductivity at a reference temperature of 10 °C test acc. to EN 12667:2001 in accordance with EN 13163:2012+A1:2015	Declared value: ¹ $\lambda_D = 0,034 \text{ W/(m} \cdot \text{K)}$
Moisture conversion coefficient	No performance assessed
Water absorption long term water absorption by total immersion test acc. to EN 12087:2013 (method 2A) with deviating drip-off time of max. 10 seconds long term water absorption by diffusion test acc. to EN 12088:2013	$\leq 5 \text{ Vol.-%}$ $\leq 10 \text{ Vol.-% (WD(V)10 acc. to EN 13163)}$
Freeze-thaw resistance test acc. to EN 12091:2013	$\leq 15 \text{ Vol.-%}^2 \text{ (FTCD15 acc. to EN 13163)}$
Water vapour diffusion resistance factor	No performance assessed

¹ The declared value is representative for at least 90 % of the production with a confidence level of 90 % and applies to the density range mentioned in section 3.

² The water absorption after freeze-thaw cycling shall not be increased by more than 15 Vol.-% and the reduction in compressive stress at 10 % deformation of the re-dried specimens, when tested in accordance with EN 826, shall not exceed 10 % of the initial value.

Essential characteristic	Performance
<p>Geometrical properties</p> <p>thickness test acc. to EN 823:2013</p> <p>length, width test acc. to EN 822:2013</p> <p>squareness on length and width test acc. to EN 824:2013</p> <p>flatness test acc. to EN 825:2013</p> <p>profiling and volume loss</p>	<p>tolerance</p> <p>± 2 mm (T(2) acc. to EN 13163)</p> <p>$\pm 0,6$ % or ± 3 mm³ (L(3) or. W(3) acc. to EN 13163)</p> <p>5 mm/m (S(5) acc. to EN 13163)</p> <p>5 mm (P(5) acc. to EN 13163)</p> <p>no performance assessed</p>
<p>Deformation under specified compressive load and temperature conditions</p> <p>test acc. to EN 1605:2013</p> <p>load: 40 kPa, temperature: (70 ± 1) °C</p> <p>time: (168 ± 1) h</p> <p>nominal thickness ≤ 200 mm:</p> <p>nominal thickness > 200 mm:</p>	<p>≤ 5 % (DLT(2)5 acc. to EN 13163)</p> <p>≤ 3 %</p>
<p>Dimensional stability under constant normal laboratory conditions</p> <p>test acc. to EN 1603:2013</p>	<p>DS(N)2 acc. to EN 13163</p>
<p>Dimensional stability under specified conditions</p> <p>test acc. to EN 1604:2013</p>	<p>DS(70,-)3 acc. to EN 13163</p>
<p>Tensile strength perpendicular to faces</p>	<p>No performance assessed</p>
<p>Bending strength</p> <p>test acc. to EN 12089:2013 (method B)</p>	<p>≥ 200 kPa (BS200 acc. to EN 13163)</p>
<p>Density</p> <p>test acc. to EN 1602:2013</p>	<p>28 kg/m³ to 35 kg/m³</p>
<p>Compressive stress at 10 % deformation</p> <p>test acc. to EN 826:2013</p>	<p>≥ 150 kPa (CS(10)150 acc. to EN 13163)</p>
<p>Compressive creep</p>	<p>No performance assessed</p>

3.7 Sustainable use of natural resources (BWR 7)

For the sustainable use of natural resources no performance was investigated for this product.

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with EAD No. 040773-00-1201, the applicable European legal act is: 1999/91/EC.

The system to be applied is:

System 3

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 7 August 2019 by Deutsches Institut für Bautechnik

Maja Tiemann
Head of Department

beglaubigt:
Meyer