

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments



European Technical Assessment

ETA-12/0142
of 18 May 2021

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

CELO Quick fix anchor BA plus

Product family
to which the construction product belongs

Mechanical fasteners for use in concrete

Manufacturer

CELO Befestigungssysteme GmbH
Industriestraße 6
86551 Aichach
DEUTSCHLAND

Manufacturing plant

Werk 11
Werk 12

Plant 11
Plant 12

This European Technical Assessment
contains

11 pages including 3 annexes which form an integral part
of this assessment

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

EAD 330232-00-0601, Edition 10/2016

This version replaces

ETA-12/0142 issued on 7 November 2018

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific Part

1 Technical description of the product

The CELO Quick fix anchor BA plus is an anchor of sizes M6, M8, M10, M12, M16 and M20 made of galvanised steel which is placed into a drilled hole and anchored by torque-controlled expansion.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi-static loading)	See Annex B2 and C 1
Characteristic resistance to shear load (static and quasi-static loading)	See Annex C 2
Displacements (static and quasi-static loading)	See Annex C 1 and C 2
Characteristic resistance and displacements for seismic performance categories C1 and C2	No performance assessed

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Class A1
Resistance to fire	No performance assessed

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with European Assessment Document EAD No. 330232-00-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable European Assessment Document


Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at Deutsches Institut für Bautechnik.

Issued in Berlin on 18 May 2021 by Deutsches Institut für Bautechnik


Dipl.-Ing. Beatrix Wittstock
Head of Section

beglaubigt:
Baderschneider


CELO Quick fix anchor BA plus (assembling)



Marking:	brand marking	Logo or company name
	Type	BA plus
	Size	M ... (i.e. M12)
	Length	L ... (i.e. 130)
	Max. thickness of fixture	t_{fix} (i.e. 30)

Example:  BA plus 12-130/30

CELO Quick fix anchor BA plus (after installation)



h_{nom}	=	setting depth
h_1	=	depth of drill hole (deepest point)
h_{min}	=	min. thickness of concrete member
t_{fix}	=	thickness of fixture
h_{ef}	=	effective anchorage depth

CELO Quick fix anchor BA plus

Product description
Marking and installed condition

Annex A1




Table 1: Designation, materials and strength

Designation	material	strength
bolt	cold form steel or free cutting steel	M6: $f_{uk} \geq 900 \text{ N/mm}^2$, $f_{yk} \geq 720 \text{ N/mm}^2$ M8: $f_{uk} \geq 750 \text{ N/mm}^2$, $f_{yk} \geq 650 \text{ N/mm}^2$ M10: $f_{uk} \geq 670 \text{ N/mm}^2$, $f_{yk} \geq 540 \text{ N/mm}^2$ M12: $f_{uk} \geq 630 \text{ N/mm}^2$, $f_{yk} \geq 500 \text{ N/mm}^2$ M16: $f_{uk} \geq 600 \text{ N/mm}^2$, $f_{yk} \geq 510 \text{ N/mm}^2$ M20: $f_{uk} \geq 510 \text{ N/mm}^2$, $f_{yk} \geq 410 \text{ N/mm}^2$
clip	cold steel strip acc. EN 10130:2006, C490, C1035/C1045	$\geq 128 \text{ HV } 10 \text{ or HV } 1$
washer	cold steel strip	$\geq 140 \text{ HV } 10 \text{ or HV } 1$
nut	Steel, size acc. DIN 934 or EN ISO 4032:2012	class 8 (EN ISO 898-2:2012)

all parts zinc plated and blue passivated $\geq 5 \mu\text{m}$ acc. EN ISO 4042:2018

Table 2: Dimensions

anchor		bolt			clip	washer		hex-nut
		length overall	length overall	bolt- \varnothing	length	thickness	outer- \varnothing	Wrench size
type	size	L	f	d_{nom}	l_s	s	d_s	SW
		[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
BA plus	M6	55 - 150	acc. drawing	6	13,3	$\geq 1,4$	≥ 12	10
BA plus	M8	65 - 365	acc. drawing	8	13,5	$\geq 1,4$	≥ 16	13
BA plus	M10	75 - 375	acc. drawing	10	20,5	$\geq 1,7$	≥ 19	17
BA plus	M12	100 - 500	acc. drawing	12	20,0	$\geq 2,2$	≥ 23	19
BA plus	M16	120 - 615	acc. drawing	16	24,0	$\geq 2,7$	≥ 29	24
BA plus	M20	160 - 640	acc. drawing	20	28,8	$\geq 2,7$	≥ 35	30

CELO Quick fix anchor BA plus

Product description
Designation, materials and anchor dimensions

Annex A2

Specification of intended use

Anchorage subject to:

- Static and quasi-static loads.

Base materials:

- Compacted reinforced or unreinforced normal weight concrete without fibres according to EN 206:2013+A1:2016.
- Strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016.
- Uncracked concrete.

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions.

Design:

- Anchorages are designed under the responsibility of an engineer experienced in anchorages and concrete work.
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.).
- Anchorages under static or quasi-static actions are designed in accordance with EN 1992-4:2018 and EOTA Technical Report TR 055, Edition February 2018

Installation:

- Anchor installation carried out by appropriately qualified personal and under the supervision of the person responsible for technical matters of the site.
- Anchor installation in accordance with the manufacturer's specifications and drawings and using the appropriate tools.
- Hole drilling by hammer drilling only.
- Positioning of the drill holes without damaging the reinforcement.

CELO Quick fix anchor BA plus

Intended use
Specification

Annex B1

Table 3: Installation data

CELO Quick fix anchor BA plus			size	size	size	size	size	size
			M6	M8	M10	M12	M16	M20
nominal driller diameter	d_0	[mm]	6	8	10	12	16	20
max. cutting diameter of drill bit	$d_{cut,max} \leq$	[mm]	6,40	8,45	10,45	12,50	16,50	20,55
depth of drill hole (deepest point)	$h_1 \geq$	[mm]	48	60	65	90	110	130
effective anchorage depth	$h_{ef} \geq$	[mm]	35	45	50	70	85	100
setting depth	$h_{nom} \geq$	[mm]	40	54	59	84	99	114
diameter of clearance hole in the fixture	$d_f \leq$	[mm]	7	9	12	14	18	22
thickness of fixture	$t_{fix,min...max}$	[mm]	0...100	0...300	0...300	0...400	0...500	0...500
wrench size of the nut	SW	[mm]	10	13	17	19	24	30
Required installation torque moment	T_{inst}	[Nm]	8	15	30	50	110	180

Table 4: Minimum thickness of concrete member, min. spacing and edge distance

CELO Quick fix anchor BA plus			size	size	size	size	size	size
			M6	M8	M10	M12	M16	M20
minimum thickness of member	h_{min}	[mm]	100	100	120	160	200	200
minimum spacing	s_{min}	[mm]	50	50	120	70	100	160
minimum edge distance	c_{min}	[mm]	50	50	90	90	100	150


CELO Quick fix anchor BA plus

Intended use


Installation data, minimum thickness, min. spacing and edge distance

Annex B2


Installation instruction of the CELO quick fix anchor BA plus




1. Drill the hole with a hammer drill




2. Clean the borehole



3. Hammer in the anchor (consider the defined setting depth)



4. Apply the required installation torque T_{inst} by using a torque wrench



5. After installation

CELO Quick fix anchor BA plus

Intended use
Installation instruction

Annex B3

Table 5: Characteristic values under tension loads

CELO Quick fix anchor BA plus			size	size	size	size	size	size
			M6	M8	M10	M12	M16	M20
Steel failure								
characteristic resistance	$N_{Rk,s}$	[kN]	12,1	17,2	27,5	40,0	70,0	109,3
partial factor	γ_{Ms}	[-]	1,5	1,4	1,49	1,51	1,41	1,5
Pull out failure								
characteristic resistance in uncracked concrete C20/25	$N_{Rk,p}$	[kN]	7,5	17	16	24	32	50
increasing factors for $N_{Rk,p}$	Ψ_c	C25/30	1,10	1,00	1,10	1,08	1,10	1,10
		C30/37	1,22	1,00	1,22	1,16	1,22	1,22
		C40/50	1,41	1,00	1,41	1,28	1,41	1,41
		C50/60	1,58	1,00	1,58	1,39	1,58	1,58
installation factor	γ_{inst}	[-]	1,0	1,0	1,0	1,0	1,2	1,2
Concrete cone failure								
effective anchorage depth	h_{ef}	[mm]	35	45	50	70	85	100
factor for uncracked concrete	$k_{ucr,N}$	[-]	11,0					
factor for cracked concrete	$k_{cr,N}$	[-]	No performance assessed					
spacing	$s_{cr,N}$	[mm]	3 h_{ef}					
edge distance	$c_{cr,N}$	[mm]	1,5 h_{ef}					
installation factor	γ_{inst}	[-]	1,0	1,0	1,0	1,0	1,2	1,2
Concrete splitting failure								
Characteristic resistance in uncracked concrete C20/25	$N^0_{Rk,sp}$	[kN]	min ($N_{Rk,p}$; $N^0_{Rk,c}$)					
spacing (splitting)	$s_{cr,sp}$	[mm]	190	190	240	390	400	400
edge distance (splitting)	$c_{cr,sp}$	[mm]	95	100	120	125	160	225
installation factor	γ_{inst}	[-]	1,0	1,0	1,0	1,0	1,2	1,2

Table 6: Displacements under tension loads

CELO Quick fix anchor BA plus			size	size	size	size	size	size
			M6	M8	M10	M12	M16	M20
tension load	N	[kN]	3,6	8,1	6,3	11,4	12,7	21,5
displacements	δ_{N0}	[mm]	0,2	1,2	1,3	1,3	0,7	0,4
displacements	$\delta_{N\infty}$	[mm]	0,6	1,6	1,9	1,6	1,6	1,5

CELO Quick fix anchor BA plus

Performances

Characteristic values under tension load, displacement

Annex C1

Table 7: Characteristic values under shear loads

CELO Quick fix anchor BA plus			size	size	size	size	size	size
			M6	M8	M10	M12	M16	M20
Steel failure with or without lever arm								
characteristic shear load resistance	$V_{RK,s}^0$	[kN]	6,4	13,7	19,4	16,8	30,6	50,5
characteristic bending moment	$M_{RK,s}^0$	[Nm]	9,8	28,1	50,1	82,6	199,8	267,5
factor	k_7	[-]	1,0	1,0	1,0	1,0	1,0	1,0
partial factor	γ_{Ms}	[-]	1,5	1,5	1,5	1,26	1,5	1,5
Concrete pryout failure								
factor for pry out failure	k_8	[-]	1,0	1,0	1,0	2,0	2,0	2,0
installation factor	γ_{inst}	[-]	1,0					
Concrete edge failure								
effective length of anchor under shear load	l_f	[mm]	35	45	50	70	85	100
effective external diameter of anchor	d_{nom}	[mm]	6	8	10	12	16	20
installation factor	γ_{inst}	[-]	1,0					

Table 8: Displacements under shear loads

CELO Quick fix anchor BA plus			size	size	size	size	size	size
			M6	M8	M10	M12	M16	M20
shear load	V	[kN]	3,1	6,5	9,2	9,6	14,8	24,0
displacements	δ_{V0}	[mm]	0,7	0,9	1,9	0,8	1,5	1,0
displacements	$\delta_{V\infty}$	[mm]	1,1	1,4	2,9	1,2	2,3	1,5

CELO Quick fix anchor BA plus

Performances

Characteristic values under shear load, displacement

Annex C2