

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments



European Technical Assessment

ETA-17/1024
of 4 January 2021

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

Butler macht's! bitumenummantelte Ausgleichs-
Schüttung, Bit Perlit Bachl, Prima bitumenummantelte
Ausgleichsschüttung, Aquapanel Ausgleichsschüttung,
Formel-Pro Dämmschüttung WD, bauline pro
Ausgleichsschüttung bituminiert, Precit bitumenveredelte
Schüttung

Product family
to which the construction product belongs

thermal insulation product made of loose fill expanded
perlite

Manufacturer

Knauf Performance Materials GmbH
Kipperstraße 19
44147 Dortmund
DEUTSCHLAND

Manufacturing plant

plant 1 (see Annex 1)

plant 2 (see Annex 1)

plant 3 (see Annex 1)

This European Technical Assessment
contains

6 pages including 1 annex which form an integral part of
this assessment

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

EAD 040461-00-1201

This version replaces

ETA-17/1024 issued on 15 June 2020

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific part

1 Technical description of the product

This European Technical Assessment applies to the thermal insulation products made of loose fill expanded perlite (EP) with the following designations, hereinafter referred to as thermal insulation.

- Butler macht's! bitumenummantelte Ausgleichs-Schüttung
- Bit Perlit Bachl
- Prima bitumenummantelte Ausgleichsschüttung
- Aquapanel Ausgleichsschüttung
- Formel-Pro Dämmschüttung WD
- bauline pro Ausgleichsschüttung bituminiert
- Precit bitumenveredelte Schüttung

The thermal insulation material is a granular, inorganic bulk good of grain sizes 0 - 6 mm made of thermally blown perlite.

The perlite grains are provided factory-made with a bitumen coating.

The European Technical Assessment has been issued for the product on the basis of agreed data/information, deposited with Deutsches Institut für Bautechnik, which identifies the product that has been assessed. The European Technical Assessment applies only to products corresponding to this agreed data/information.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The thermal insulation material can be used in the compressed state as interior insulation of ceilings or floor slabs (on the top) under screed without requirements for protection against noise.

The performance according to section 3 only applies if the insulation product is installed according to the manufacture's installation instructions dry and in a compressed state with a compression at least 10 % by volume in accordance with the bulk density given in the ETA and if it is protected from precipitation, wetting or weathering in built-in state and during transport, storage and installation.

For the determination of the thermal resistance, the thickness of the thermal insulation material is applied, taking into account the compression.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the insulation product of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the manufacturer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

For sampling, conditioning and testing the provisions of the EAD No 040461-00-1201 "Thermal insulation product made of loose fill expanded perlite (EP)" apply.

English translation prepared by DIBt

3.1 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire test acc. to EN ISO 11925-2:2010*	Class E acc. to EN 13501-1:2007 + A1:2009
Determination of the organic content test acc. to EN 13820 (determination of combustion loss)	No performance assessed.
* Using a suitable sample holder in line with EN ISO 11925-2 in which the loose sample material cannot fall out.	

3.2 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
Content, emission and/or release of dangerous substances	
Substance/s classified as EU-cat. Carc. 1A and/or 1B ^a	The product does not contain these dangerous substances actively used. ^b However, the product may contain PAH and B[a]P as residues (see below).
Substance/s classified as EU-cat. Muta. 1A and/or 1B ^a	
Substance/s classified as EU-cat. Acute Tox. 1, 2 and/or 3; Repr. 1A and/or 1B; STOT SE 1 and/or STOT RE 1 ^a	
PAH and B[a]P	The content of these residues was tested in the raw material: ^c PAH < 50 mg/kg B[a]P < 5 mg/kg
Use scenarios regarding BWR 3 in accordance with EOTA TR 034: IA2	
^{a.} In accordance with Regulation (EC) No 1272/2008. ^{b.} Assessment based on the detailed manufacturers' statements on dangerous substances. ^{c.} Statement according to test report.	

3.3 Energy economy and heat retention (BWR 6)

Wesentliches Merkmal	Leistung
Thermal conductivity (in the compressed state) test acc. to EN 12667:2001, acc. to EN 14316-1:2004	Declared value of thermal conductivity $\lambda_D (23/50) = 0.058 \text{ W}/(\text{m} \cdot \text{K})^a$
Loose bulk density (in the uncompressed state) test acc. to EN 1097-3:1998	132 kg/m ³ to 197 kg/m ³
Particle size distribution	No performance assessed.
Water repellency	No performance assessed.
Crushing resistance	No performance assessed.
Water vapour diffusion resistance factor acc. to EN 14316-1:2004	$\mu = 3$
Settlement	No performance assessed.
Compressive stress at 10 % deformation test acc. to EN 826:2013 ^b	$\geq 90 \text{ kPa}$
^a Declared value of thermal conductivity for a moisture content of the insulation product at 23 °C/50% relative humidity, representative of at least 90% of production with a 90% confidence level. ^b The test material is compressed by 10% by volume before the test. The test frame has an open width of approx. 200 mm x 200 mm. The filling level of the compressed test material is limited to approx. 50 mm of height.	

English translation prepared by DIBt

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with the European Assessment Document No 040461-00-1201 "Thermal insulation product made of loose fill expanded perlite (EP)" the legal basis is: Commission Decision 1999/91/EC.

The system to be applied is: system 3.

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 4 January 2021 by Deutsches Institut für Bautechnik

Frank Iffländer
Head of Section

beglaubigt:
Getzlaff

Butler macht's! bitumentummantelte Ausgleichs-Schüttung,
Bit Perlit Bachl, Prima bitumentummantelte
Ausgleichsschüttung, Aquapanel Ausgleichsschüttung,
Formel-Pro Dämmschüttung WD, bauline pro
Ausgleichsschüttung bituminiert, Precit bitumenveredelte
Schüttung

Annex 1

Manufacturing plant

plant 1 Knauf Performance Materials GmbH
Kipperstraße 19
44147 Dortmund
DEUTSCHLAND

plant 2 Knauf Performance Materials GmbH
Ruhrstraße 8
86633 Neuburg/Donau
DEUTSCHLAND

plant 3 Knauf Performance Materials GmbH
Hauptstraße 102
39345 Bülstringen
DEUTSCHLAND