

Approval body for construction products  
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and  
Laender Governments



## European Technical Assessment

**ETA-22/0794**  
**of 9 December 2022**

English translation prepared by DIBt - Original version in German language

### General Part

Technical Assessment Body issuing the  
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

PROFIX concrete screw PBS-R / PBS-HCR

Product family  
to which the construction product belongs

Mechanical fasteners for use in concrete

Manufacturer

PROFIX AG  
Kanalstraße 23  
4415 LAUSEN  
SCHWEIZ

Manufacturing plant

Herstellwerk 7

This European Technical Assessment  
contains

19 pages including 3 annexes which form an integral part  
of this assessment

This European Technical Assessment is  
issued in accordance with Regulation (EU)  
No 305/2011, on the basis of

EAD 330232-01-0601, Edition 05/2021

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

**Specific Part****1 Technical description of the product**

The PROFIX concrete screw PBS-R / PBS-HCR is an anchor in size 6, 8 and 10 mm made of stainless steel. The anchor is screwed into a predrilled cylindrical drill hole. The special thread of the anchor cuts an internal thread into the member while setting. The anchorage is characterised by mechanical interlock in the special thread.

Product and product description are given in Annex A.

**2 Specification of the intended use in accordance with the applicable European Assessment Document**

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

**3 Performance of the product and references to the methods used for its assessment****3.1 Mechanical resistance and stability (BWR 1)**

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi-static loading)	See Annex B4, C1 and C2
Characteristic resistance to shear load (static and quasi-static loading)	See Annex C1 and C2
Displacements (static and quasi-static loading)	See Annex C5
Characteristic resistance and displacements for seismic performance categorie C1	See Annex C3

**3.2 Safety in case of fire (BWR 2)**

Essential characteristic	Performance
Reaction to fire	Class A1
Resistance to fire	See Annex C4

**3.3 Aspects of durability linked with the Basic Works Requirements**

Essential characteristic	Performance
Durability	See Annex B1

**4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base**

In accordance with European Assessment Document EAD No. 330232-01-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1

**5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable European Assessment Document**

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at Deutsches Institut für Bautechnik.

Issued in Berlin on 9 December 2022 by Deutsches Institut für Bautechnik


Dipl.-Ing. Beatrix Wittstock  
Head of Section

*beglaubigt:*  
Tempel


Product in installed condition

PROFIX concrete screw PBS-R / PBS-HCR

- stainless steel A4
- high corrosion resistant steel HCR



e.g. PBS-SS-R concrete screw with hexagon head and fixture



- $d_0$  = nominal diameter of drill hole


$t_{fix}$  = thickness of fixture

$d_f$  = diameter of clearance hole
- $h_{min}$  = minimum thickness of member

$h_{nom}$  = nominal embedment depth

$h_0$  = depth of drill hole


$h_{ef}$  = effective embedment depth




PROFIX concrete screw PBS-R / PBS-HCR

Product description  
Product in installed condition


Annex A1




Version with metric connection thread  
and hexagon drive e.g. PBS-ST-R 8/M10x20x105




Version with washer and hexagon head  
e.g. PBS-SS-R 8/10x80




Version with washer, hexagon head and  
TORX drive e.g. PBS-SST-R 8/10x80




Version with hexagon head  
e.g. PBS-S-R 8/10x80



Version with countersunk head and TORX drive  
e.g. PBS-F-R 8/10x80




Version with pan head and TORX  
drive e.g. PBS-P-R 8/10x80





Version with large pan head and TORX  
drive e.g. PBS-MS-R 8/10x80



Version with countersunk head and  
connection thread e.g. PBS-STF-R 6/M8x55



Version with hexagon drive and  
connection thread e.g. PBS-STF-R 6/M8x55



Version with internal thread and  
hexagon drive e.g. PBS-I-R 6/7.5x55/M8/M10

PROFIX concrete screw PBS-R / PBS-HCR

**Product description**  
Screw types

**Annex A2**

Table 1: Material

Part	Product name	Material		
all types	PROFIX PBS-R	1.4401; 1.4404; 1.4571; 1.4578		
	PROFIX PBS-HCR	1.4529		
Part	Product name	Nominal characteristic steel		Rupture elongation $A_5$ [%]
		Yield strength $f_{yk}$ [N/mm <sup>2</sup> ]	Ultimate strength $f_{uk}$ [N/mm <sup>2</sup> ]	
all types	PROFIX PBS-R	560	700	≤ 8
	PROFIX PBS-HCR			

Table 2: Dimensions


PBS concrete screw size			6			8			10		
Nominal embedment depth	$h_{nom}$		1 <sup>1)</sup>	2	3	1	2	3	1	2	3
	[mm]		35	45	55	45	55	65	55	75	85
Screw length	≤ L	[mm]	500								
Core diameter	$d_k$	[mm]	5,1			7,2			9,2		
Thread outer diameter	$d_s$	[mm]	7,6			10,5			12,5		
Thickness of filling washer	$t_v$	[mm]	5			5			5		

<sup>1)</sup> only for statically indeterminate non-structural systems (multiple use) according to EN 1992-4:2018, only in dry internal conditions

#### Marking:


##### PROFIX PBS-R

Screw type: PBS-R  
Screw size: 10  
Screw length: 100  
Material: A4



##### PROFIX PBS-HCR

Screw type: PBS-HCR  
Screw size: 10  
Screw length: 100  
Material: HCR



PROFIX concrete screw PBS-R / PBS-HCR

#### Product description

Material, dimensions and markings

Annex A3

## Specification of Intended use

Table 3: Anchorages subject to

PBS concrete screw size		6			8			10		
Nominal embedment depth	$h_{nom}$	$h_{nom1}$ <sup>1)</sup>	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$
	[mm]	35	45	55	45	55	65	55	75	85
Static and quasi-static loads		All sizes and all embedment depths								
Fire exposure										
C1 category - seismic		x	ok	ok	ok	x	ok	ok	x	ok

<sup>1)</sup> only for statically indeterminate non-structural systems (multiple use) according to EN 1992-4:2018, only in dry internal conditions

x no performance assessed

### Base materials:

- Compacted reinforced and unreinforced concrete without fibers according to EN 206:2013.
- Strength classes C20/25 to C50/60 according to EN 206:2013.
- Cracked and uncracked concrete.

### Use conditions (Environmental conditions):

- Structures subject to dry, internal conditions: all screw types.
- For all other conditions corresponding to corrosion resistance classes CRC according to EN 1993-1-4:2006 + A1:2015
  - Stainless steel according to Annex A3, screw with marking A4: CRC III
  - High corrosion resistant steel according to Annex A3, screw with marking HCR: CRC V

PROFIX concrete screw PBS-R / PBS-HCR

Intended use  
Specification

Annex B1



## Specification of Intended use - continuation

### Design:

- Anchorages are to be designed under the responsibility of an engineer experienced in anchorages and concrete work.
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.).
- Anchorages are designed according to EN 1992-4:2018 and EOTA Technical Report TR 055, Edition February 2018.

The design for shear load according to EN 1992-4:2018, Section 6.2.2 applies for all specified diameters  $d_f$  of clearance hole in the fixture in Annex B3, Table 4.

### Installation:

- Hammer drilling or hollow drilling. Hollow drilling only for size 8-10.
- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters on site.
- In case of aborted hole: new drilling must be drilled at a minimum distance of twice the depth of aborted hole or closer, if the aborted hole is filled with high strength mortar and only if the hole is not in the direction of the oblique tensile or shear load.
- After installation further turning of the anchor must not be possible. The head of the anchor is supported in the fixture and is not damaged.
- The borehole may be filled with injection mortar CF-T 300V or ATA 2004C.
- Adjustability according to Annex B6 for sizes 6-10.
- Cleaning of borehole is not necessary, if using a hollow drill.

**PROFIX concrete screw PBS-R / PBS-HCR**


**Intended use**  
Specification continuation

**Annex B2**

Table 4: Installation parameters

PBS concrete screw size			6			8			10		
Nominal embedment depth		h <sub>nom</sub>	h <sub>nom1</sub> <sup>1)</sup>	h <sub>nom2</sub>	h <sub>nom3</sub>	h <sub>nom1</sub>	h <sub>nom2</sub>	h <sub>nom3</sub>	h <sub>nom1</sub>	h <sub>nom2</sub>	h <sub>nom3</sub>
		[mm]	35	45	55	45	55	65	55	75	85
Nominal drill hole diameter	d <sub>0</sub>	[mm]	6			8			10		
Cutting diameter of drill bit	d <sub>cut</sub> ≤	[mm]	6,40			8,45			10,45		
Depth of drill hole	h <sub>0</sub> ≥	[mm]	40	50	60	55	65	75	65	85	95
Clearance hole diameter	d <sub>f</sub> ≤	[mm]	8			12			14		
Installation torque (version with connection thread)	T <sub>inst</sub>	[Nm]	10			20			40		
Torque impact screw driver		[-]	Max. torque according to manufacturer's instructions								
			160			300			450		

<sup>1)</sup> only for statically indeterminate non-structural systems (multiple use) according to EN 1992-4:2018, only in dry internal conditions



PROFIX concrete screw PBS-R / PBS-HCR

Intended use  
Installation parameters

Annex B3

Table 5: Minimum thickness of member, minimum edge distance and minimum spacing

PBS concrete screw size			6			8			10		
Nominal embedment depth	$h_{nom}$		$h_{nom1}^{1)}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$
	[mm]		35	45	55	45	55	65	55	75	85
Minimum thickness of member	$h_{min}$	[mm]	80	80	100	80	100	120	100	130	130
Minimum edge distance	$c_{min}$	[mm]	35	35	35	35	35	35	40	40	40
Minimum spacing	$s_{min}$	[mm]	35	35	35	35	35	35	40	40	40

<sup>1)</sup> only for statically indeterminate non-structural systems (multiple use) according to EN 1992-4:2018, only in dry internal conditions

**PROFIX concrete screw PBS-R / PBS-HCR**


**Intended use**

Minimum thickness of member, minimum edge distance and minimum spacing

**Annex B4**


## Installation Instructions

1




Create hammer drilled or hollow drilled borehole

2




Remove drill dust by vacuuming or blowing of

3



Install with torque impact screw driver or torque wrench

4



The head must be undamaged and in contact with the fixture

For screw size 6 with  $h_{nom} = 35\text{mm}$ , installation only with impact screw drivers.


PROFIX concrete screw PBS-R / PBS-HCR

Intended use  
Installation instructions


Annex B5

## Installation Instructions – Adjustment


### 1. Adjustment



Screw may be untightened maximum 10mm




After adjustment, tighten the screw again




The head must be undamaged and in contact with the fixture


### 2. Adjustment



Screw may be untightened maximum 10mm



After adjustment, tighten the screw again



The head must be undamaged and in contact with the fixture

#### Note:

The fastener can be adjusted maximum two times. The total allowed thickness of shims added during the adjustment process is 10mm. The final embedment depth after adjustment process must be larger or equal than  $h_{nom}$ .

PROFIX concrete screw PBS-R / PBS-HCR





#### Intended use

Installation instructions - Adjustment


Annex B6

## Installation Instructions – Filling annular gap

### Positioning of fixture and filling washer



### Filling the annular gap



#### Note:

For seismic loading the installation with filled and without filled annular gap is approved. Differences in performance can be found in Annex C3.

**PROFIX concrete screw PBS-R / PBS-HCR**

#### Intended use

Installation instructions – Filling annular gap

**Annex B7**



Table 6: Characteristic values for static and quasi-static loading

PBS concrete screw size			6			8			10			
Nominal embedment depth	$h_{nom}$	$h_{nom1}^{1)}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$		
	[mm]	35	45	55	45	55	65	55	75	85		
Steel failure for tension and shear loading												
Characteristic tension load	$N_{Rk,s}$	[kN]	14,0			27,0			45,0			
Characteristic shear load	$V_{Rk,s}^0$	[kN]	7,0			13,5		17,0	22,5	34,0		
Ductility factor	$k_7$	[-]	0,8									
Characteristic bending load	$M_{Rk,s}^0$	[Nm]	10,9			26,0			56,0			
Pull-out failure in uncracked concrete												
Characteristic tension load C20/25		$N_{Rk,p}$	[kN]	3,5 <sup>1)</sup>	4,0	8,5	9,0	12,0	17,0	11,0	19,0	25,0
Increasing factor for $N_{Rk,p} = N_{Rk,p (C20/25)} \cdot \Psi_c$	C25/30	$\Psi_c$	[-]	1,08	1,12	1,09	1,12		1,07	1,12		
	C30/37			1,15	1,22	1,17	1,22		1,13	1,22		
	C40/50			1,27	1,41	1,30	1,41		1,23	1,41		
	C50/60			1,38	1,58	1,42	1,58		1,32	1,58		
Pull-out failure in cracked concrete												
Characteristic tension load C20/25		$N_{Rk,p}$	[kN]	2,5 <sup>1)</sup>	1,5	3,0	3,0	5,5	8,0	6,0	13,0	17,0
Increasing factor for $N_{Rk,p} = N_{Rk,p (C20/25)} \cdot \Psi_c$	C25/30	$\Psi_c$	[-]	1,10	1,08	1,12	1,12		1,12		1,09	
	C30/37			1,18	1,15	1,22	1,22		1,22		1,17	
	C40/50			1,32	1,27	1,41	1,41		1,41		1,31	
	C50/60			1,45	1,38	1,58	1,58		1,58		1,43	
1) only for statically indeterminate non-structural systems (multiple use) according to EN 1992-4:2018, only in dry internal conditions												
PROFIX concrete screw PBS-R / PBS-HCR										Annex C1		
Performances Characteristic values for static and quasi-static loading												

Table 7: Characteristic values for static and quasi-static loading continuation

PBS concrete screw size				6			8			10		
Nominal embedment depth		$h_{nom}$	$h_{nom1}^{1)}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$	
		[mm]	35	45	55	45	55	65	55	75	85	
Concrete failure: concrete cone failure and splitting failure												
Effective embedment depth		$h_{ef}$	[mm]	25	34	42	32	41	49	40	57	65
k-factor	cracked	$k_{cr}$	[-]	7,7								
	uncracked	$k_{ucr}$	[-]	11,0								
Concrete cone failure	spacing	$s_{cr,N}$	[mm]	3 x $h_{ef}$								
	edge distance	$c_{cr,N}$	[mm]	1,5 x $h_{ef}$								
Splitting failure case 1	resistance	$N^0_{Rk,sp}$	[kN]	3,5 <sup>1)</sup>	4,0	8,5	9,0	12,0	17,0	11,0	19,0	25,0
	spacing	$s_{cr,sp}$	[mm]	120	160	240	200	240	290	230	280	320
	edge distance	$c_{cr,sp}$	[mm]	60	80	120	100	120	145	115	140	160
Splitting failure case 2	resistance	$N^0_{Rk,sp}$	[kN]	2 <sup>2)</sup>	2,5	5,5	5,5	8,0	11,0	7,0	15,0	20,0
	spacing	$s_{cr,sp}$	[mm]	2 <sup>2)</sup>	116	168	128	164	196	160	224	260
	edge distance	$c_{cr,sp}$	[mm]	2 <sup>2)</sup>	58	84	64	82	98	80	114	130
Pry-out failure												
Factor for pry-out failure		$k_g$	[-]	1,0	1,6	2,1	2,8	2,5				
Installation factor		$\gamma_{inst}$	[-]	1,0								
Concrete edge failure												
Effective length in concrete		$l_f$	[mm]	35	45	55	45	55	65	55	75	85
Nominal outer diameter of screw		$d_{nom}$	[mm]	6			8			10		

<sup>1)</sup> only for statically indeterminate non-structural systems (multiple use) according to EN 1992-4:2018, only in dry internal conditions

<sup>2)</sup> no performance assessed

PROFIX concrete screw PBS-R / PBS-HCR

**Performances**

Characteristic values for static and quasi-static loading continuation

**Annex C2**



Table 8: Seismic category C1 – Characteristic load values (PBS-SS-R, PBS-SST-R, PBS-S-R, PBS-F-R, PBS-ST-R, PBS-STF-R, PBS-STS-R<sup>1)</sup>, PBS-P-R, PBS-MS-R und PBS-I-R<sup>1)</sup>)

PBS concrete screw size			6		8		10	
Nominal embedment depth	$h_{nom}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom3}$	$h_{nom1}$	$h_{nom3}$	
	[mm]	45	55	45	65	55	85	
Steel failure for tension and shear load (version <b>Typ PBS-SS-R / SST-R / S-R / F-R / ST-R / STF-R / STS-R<sup>1)</sup> / P-R / MS-R und I-R<sup>1)</sup></b> )								
Characteristic tension load	$N_{Rk,s,C1}$	[kN]	14,0		27,0		45,0	
Partial factor	$\gamma_{Ms,N}$	[-]	1,5					
Characteristic shear load <b>Typ PBS-SS-R / SST-R / S-R</b> <b>Typ PBS-ST-R / STF-R / STS-R</b> <b>Typ PBS-P-R / MS-R</b>	$V_{Rk,s,C1}$	[kN]	3,5	4,0	8,0	10,0	14,0	16,0
Characteristic shear load <b>PBS-F-R</b>	$V_{Rk,s,C1}$	[kN]	2,5	2)	4,5	7,0	14,0	10,0
Partial factor	$\gamma_{Ms,V}$	[-]	1,25					
Without filling of the annular gap <sup>3)</sup>	$\alpha_{gap}$	[-]	0,5					
With filling of the annular gap <sup>4)</sup>	$\alpha_{gap}$	[-]	1,0					
Pull-out failure (version <b>Typ PBS-SS-R / SST-R / S-R / F-R / ST-R / STF-R / STS-R<sup>1)</sup> / P-R / MS-R und I-R<sup>1)</sup></b> )								
Characteristic tension load in cracked concrete C20/25	$N_{Rk,p,C1}$	[kN]	1,5	3,0	3,0	8,5	6,0	17,0
Concrete cone failure (version <b>Typ PBS-SS-R / SST-R / S-R / F-R / ST-R / STF-R / STS-R<sup>1)</sup> / P-R / MS-R und I-R<sup>1)</sup></b> )								
Effective embedment depth	$h_{ef}$	[mm]	34	42	32	49	40	65
Edge distance	$c_{cr,N}$	[mm]	1,5 x $h_{ef}$					
Spacing	$s_{cr,N}$	[mm]	3 x $h_{ef}$					
Installation safety factor	$\gamma_{inst}$	[-]	1,0					
Concrete pry-out failure (version <b>Typ PBS-SS-R / SST-R / S-R / F-R / ST-R / P-R / MS-R</b> )								
Factor for pry-out failure	$k_8$	[-]	1,6		2,1	2,8	2,5	
Concrete edge failure (version <b>Typ PBS-SS-R / SST-R / S-R / F-R / ST-R / P-R / MS-R</b> )								
Effective length in concrete	$l_f$	[mm]	45	55	45	65	55	85
Nominal outer diameter of screw	$d_{nom}$	[mm]	6		8		10	

<sup>1)</sup> only tension load

<sup>2)</sup> no performance assessed

<sup>3)</sup> without filling of the annular gap according to annex B5

<sup>4)</sup> with filling of the annular gap according to annex B7

**PROFIX concrete screw PBS-R / PBS-HCR**

**Performances**

Seismic category C1 – Characteristic load values

**Annex C3**

Table 9: Fire exposure – characteristic values of resistance

PBS concrete screw size				6			8			10		
Nominal embedment depth			$h_{nom}$	1 <sup>1)</sup>	2	3	1	2	3	1	2	3
			[mm]	35	45	55	45	55	65	55	75	85
Steel failure for tension and shear load												
characteristic Resistance	R30	$N_{Rk,s,fi30}$	[kN]	0,9			2,4			4,4		
	R60	$N_{Rk,s,fi60}$	[kN]	0,8			1,7			3,3		
	R90	$N_{Rk,s,fi90}$	[kN]	0,6			1,1			2,3		
	R120	$N_{Rk,s,fi120}$	[kN]	0,4			0,7			1,7		
	R30	$V_{Rk,s,fi30}$	[kN]	0,9			2,4			4,4		
	R60	$V_{Rk,s,fi60}$	[kN]	0,8			1,7			3,3		
	R90	$V_{Rk,s,fi90}$	[kN]	0,6			1,1			2,3		
	R120	$V_{Rk,s,fi120}$	[kN]	0,4			0,7			1,7		
	R30	$M^0_{Rk,s,fi30}$	[Nm]	0,7			2,4			5,9		
	R60	$M^0_{Rk,s,fi60}$	[Nm]	0,6			1,8			4,5		
	R90	$M^0_{Rk,s,fi90}$	[Nm]	0,5			1,2			3,0		
	R120	$M^0_{Rk,s,fi120}$	[Nm]	0,3			0,9			2,3		
Pull-out failure												
characteristic Resistance	R30-90	$N_{Rk,p,fi}$	[kN]	0,6	0,4	0,8	0,8	1,4	2,0	1,5	3,3	4,3
	R120	$N_{Rk,p,fi}$	[kN]	0,5	0,3	0,6	0,6	1,1	1,6	1,2	2,6	3,4
Concrete cone failure												
characteristic Resistance	R30-90	$N^0_{Rk,c,fi}$	[kN]	0,5	1,2	2,0	1,0	1,9	2,9	1,7	4,2	5,9
	R120	$N^0_{Rk,c,fi}$	[kN]	0,4	0,9	1,6	0,8	1,5	2,3	1,4	3,4	4,7
Edge distance												
R30 - R120		$C_{cr,fi}$	[mm]	2 x $h_{ef}$								
In case of fire attack from more than one side, the minimum edge distance shall be $\geq 300\text{mm}$ .												
Spacing												
R30 bis R120		$S_{cr,fi}$	[mm]	4 x $h_{ef}$								
Pry-out failure												
R30 bis R120		$k_8$	[-]	1,0	1,6	2,1	2,8	2,5				
The anchorage depth has to be increased for wet concrete by at least 30 mm compared to the given value.												
<sup>1)</sup> only for statically indeterminate non-structural systems (multiple use) according to EN 1992-4:2018, only in dry internal conditions												
PROFIX concrete screw PBS-R / PBS-HCR										Annex C4		
Performances Fire exposure – characteristic values of resistance												

Table 10: Displacements under static and quasi-static tension load

PBS concrete screw size				6		8			10		
Nominal embedment depth			$h_{nom}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$
			[mm]	45	55	45	55	65	55	75	85
Cracked concrete	tension load	N	[kN]	0,72	1,45	1,63	2,74	4,06	3,04	6,22	8,46
	displacement	$\delta_{N0}$	[mm]	0,19	0,27	0,27	0,53	0,45	0,26	0,58	0,61
		$\delta_{N\infty}$	[mm]	0,55	0,84	0,49	0,66	0,61	0,69	0,92	1,1
Uncracked concrete	tension load	N	[kN]	2,11	4,07	4,24	5,97	8,03	5,42	9,17	12,28
	displacement	$\delta_{N0}$	[mm]	0,42	0,43	0,33	0,49	0,58	0,84	0,62	0,79
		$\delta_{N\infty}$	[mm]	0,42	0,43	0,58			0,79		

Table 11: Displacements under static and quasi-static shear load

PBS concrete screw size				6		8			10		
Nominal embedment depth			$h_{nom}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$	$h_{nom1}$	$h_{nom2}$	$h_{nom3}$
			[mm]	45	55	45	55	65	55	75	85
Cracked and uncracked concrete	shear load	V	[kN]	3,3		8,6			16,2		
	displacement	$\delta_{V0}$	[mm]	1,55		2,7			2,7		
		$\delta_{V\infty}$	[mm]	3,1		4,1			4,3		

PROFIX concrete screw PBS-R / PBS-HCR

**Performances**  
Displacements under static and quasi-static loads

**Annex C5**