

Public-law institution jointly founded by the federal states and the Federation

European Technical Assessment Body  
for construction products



European Technical  
Assessment

ETA-25/0220  
of 22 September 2025

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the European Technical Assessment:	Deutsches Institut für Bautechnik
Trade name of the construction product	StoFloor Balcony Waterproof EB 200 reinforced
Product family to which the construction product belongs	Liquid applied roof waterproofing on the basis of polyurethane
Manufacturer	StoCretec GmbH Gutenbergstraße 6 65830 Kriftel GERMANY
Manufacturing plant	Sto SE & Co. KGaA Werk 008; Werk 002; Werk 169
This European Technical Assessment contains	8 pages including 3 annexes which form an integral part of this assessment
This European Technical Assessment is issued in accordance with Regulation (EU) No 305/2011, on the basis of	EAD 030350-00-0402

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

## Specific part

### 1 Technical description of the product

The liquid applied roof waterproofing "StoFloor Balcony Waterproof EB 200 reinforced" is a kit, which consists of the following components:

- Primer "StoPox 452 EP".
- Scatter with quartz sand "StoQuarz 0,3-0,8 mm".
- Liquid waterproofing on the basis of a polyurethane "StoPur EB 200".
- Polyester non-woven "StoDivers N 020/030/100" as reinforcement.

As an assembled system these components form a homogeneous seamless roof waterproofing.

The minimum layer thickness of the roof waterproofing applied (with reinforcement) is 3.3 mm.

For an adequate adhesion of the waterproofing layer – depending on the type of substrate – a primer is required. In general, the primer belonging to the substrate is given in the manufacturer technical documents<sup>1</sup>. In single cases the manufacturer is responsible to give guidance which pretreatment/primer is required.

The liquid applied roof waterproofing materials can be applied by pouring and/or brushing.

The liquid applied roof waterproofing "StoFloor Balcony Waterproof EB 200 reinforced" does not contain any substances that are intended to inhibit or prevent root penetration (root protection agents)<sup>2</sup>.

The components and the system build-up of the roof waterproofing are given in Annex A1.

### 2 Specification of the intended use in accordance with the applicable European Assessment Document

The liquid applied roof waterproofing is used for the waterproofing of roof surfaces, terraces and balconies.

In the technical documents the manufacturer gives information concerning the substrates which the product is suitable for and on how these substrates shall be pre-treated.

The product can be used for new roofs or for upgrading existing roof waterproofing. It can also be used on vertical surfaces (singular details).

The levels of use categories and the performance of the product are given in Annex A2.

The verification and assessment methods on which this European Technical Assessment is based lead to the assumption of working life of the product of 25 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

The levels of use categories and performances given in Section 3 are only valid if the liquid applied roof waterproofing is used in compliance with the specifications and conditions given in Annex B and the installation instructions of the manufacturer stated in the technical documents.

### 3 Performance of the product and references to the methods used for its assessment

#### 3.1 Safety in case of fire (BWR 2)

Essential characteristic	Performance
External fire performance of roofs	See Annex A2
Reaction to fire	See Annex A2

<sup>1</sup> The manufacturer's technical documents comprise all information necessary for the production and the installation of the product as well as for repair of the roof waterproofing made from that and it is deposited with DIBt.

<sup>2</sup> Manufacturer's statement.

### 3.2 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
Content, emission and/or release of dangerous substances	None of these raw materials are actively used in the manufacture of the construction product <sup>b)</sup>
Substance/s classified as EU-cat. Carc. 1A and/or 1B <sup>a)</sup>	
Substance/s classified as EU-cat. Muta. 1A and/or 1B <sup>a)</sup>	
Substance/s classified as EU-cat. Repr. 1A and/or 1B <sup>a)</sup>	
Release scenario regarding BWR 3: S/W 2	
Resistance to water vapour	See Annex A2
Watertightness	See Annex A2
Resistance to wind loads	See Annex A2
Resistance to mechanical damage (perforation)	See Annex A2
Resistance to fatigue movement	See Annex A2
Resistance to the effects of low and high surface temperature	See Annex A2
Resistance to ageing media (heat and water)	See Annex A2
Resistance to UV radiation in the presence of moisture (climatic zone)	See Annex A2
Resistance to plant roots	No performance assessed
Effects of variations in kit components and site practices	See Annex A2
Effects of day joints	See Annex A2

<sup>a)</sup> In accordance with Regulation (EC) No 1272/2008

<sup>b)</sup> Assessment based on the detailed manufacturer's statements on dangerous substances.

### 3.3 Safety and accessibility in use (BWR 4)

Essential characteristic	Performance
Slipperiness	No performance assessed

### 3.4 General aspects

The verification of durability and serviceability is part of testing the essential characteristics. Durability and serviceability are only ensured if the specifications of intended use according to Annex B and the specifications of the technical documents of the manufacturer are kept.

**4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base**

In accordance with EAD No. 030350-00-0402, the applicable European legal act is: 98/599/EC as amended by Commission Decision 2001/596/EC.

The system to be applied is: 3

In addition, with regard to external fire performance of roofs and reaction to fire for products covered by this EAD the system to be applied is: 3

**5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD**


Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 22 September 2025 by Deutsches Institut für Bautechnik

Bettina Hemme  
Head of Section

*beglaubigt:*  
Hannoun

System built-up:



No.	Description	Product/component	Consumption / weight / dimensions
1	Substrate	-	-
2	Primer	"StoPox 452 EP"	approx. 300 g/m <sup>2</sup>
3	Scatter	"StoQuarz 0,3-0,8 mm"	approx. 1000 g/m <sup>2</sup>
4	1 <sup>st</sup> layer of liquid waterproofing	"StoPur EB 200"	see No. 6
5	Reinforcement	"StoDivers N 020/030/100"	Weight per unit area:110 ±10 g/m <sup>2</sup> Width: "N 020": 200 mm "N 030": 330 mm "N 100": 1000 mm
6	2 <sup>nd</sup> layer of liquid waterproofing	"StoPur EB 200"	Total consumption of 1 <sup>st</sup> + 2 <sup>nd</sup> layer: ≥ 3500 g/m <sup>2</sup>

StoFloor Balcony Waterproof EB 200 reinforced  
StoCretec GmbH

System built-up

Annex A1

Description of the product			
Minimum thickness of the Waterproofing			3.3 mm
Minimum quantity consumed:			3500 g/m²
Roof slope			S1 to S4 (each slope)
Essential characteristics			Performance / use categories
External fire performance of roofs		EN 13501-5	Class B <sub>ROOF</sub> (t1)*
Reaction to fire		EN 13501-1	Class E
Content, emission and/or release of dangerous substances			See section 3.2
Water vapour diffusion resistance factor			μ ≈ 24000
Watertightness			Watertight
Resistance to wind loads (hard substrates, e.g., concrete or steel)			≥ 50 kPa
Resistance to mechanical damage (perforation) (hard substrates, e.g., concrete or steel)			P1 to P4 (from low to high/special)
Resistance to fatigue movement			W3
Resistance to the effects of	low surface temperature		TL4 (-30 °C)
	high surface temperature		TH4 (+90 °C)
Working life according to the resistance to ageing media (heat and water)			W3 (25 years)
UV resistance in presence of moisture (climatic zone)			M and S (moderate and severe climates)
Resistance to plant roots			No performance assessed
Effects of variations in kit components and site practices (application temperatures)	at +10 °C and at +30 °C	Maximum tensile strength	3.0 MPa (±20 %)
		Elongation	11 % (±25 %)
		Dynamic indentation	P4
Effects of day joints			≥ 50 kPa
Resistance to slipperiness			No performance assessed

\* Class **B<sub>ROOF</sub> (t1)**

The classification is valid for the following supporting decks:

- to roofs with pitches < 20°.
- any non-combustible continuous deck with a minimum thickness of 10 mm.
- any other roof systems for which classification documents for B<sub>ROOF</sub> (t1) according to EN 13501-5 are available.

**StoFloor Balcony Waterproof EB 200 reinforced**  
StoCretec GmbH

**Description, levels of use categories and performances of the product**

Annex A2

## Installation

The levels of use categories and the performances of the roof waterproofing can be assumed only, if the installation is carried out according to the installation instructions stated in the technical documents of the manufacturer, in particular taking account of the following points:

- installation by appropriately trained personnel;
- installation of only those components which are marked components of the kit;
- installation with the required tools and adjuvants;
- precautions during installation;
- inspecting the roof surface for cleanliness and correct preparation, if need be, applying a primer before applying the product;
- inspecting compliance with suitable weather and curing conditions;
- ensuring a thickness of the cured waterproofing of at least 3.3 mm by processing appropriate minimum quantities of material;
- inspections during installation and of the finished product and documentation of the results.

**StoFloor Balcony Waterproof EB 200 reinforced**  
StoCretec GmbH

**Intended use**  
Specifications for the installation

Annex B