

Public-law institution jointly founded by the
federal states and the Federation

**European Technical Assessment Body
for construction products**



European Technical Assessment

**ETA-10/0180
of 27 May 2026**

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

Expandet Throughbolt EXG II

Product family
to which the construction product belongs

Mechanical fastener for use in concrete

Manufacturer

Kyocera Fastening Solutions A/S
Svendbuen 2
3230 GRAESTED
DENMARK

Manufacturing plant

Werk 1, Germany

This European Technical Assessment
contains

15 pages including 3 annexes which form an integral part
of this assessment

This European Technical Assessment is
issued in accordance with Article 95(4) of
Regulation (EU) 2024/3110, on the basis of

EAD 330232-02-0601

This version replaces

ETA-10/0180 issued on 25 September 2015

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 36(3) of Regulation (EU) No 2024/3110.

Specific Part

1 Technical description of the product

The Expandet Throughbolt EXG II is a fastener made of zinc coated steel or stainless steel which is placed into a drilled hole and anchored by application of the installation torque.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the fastener is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the fastener of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi static loading) Method A	See Annex B4, C1 and C2
Characteristic resistance to shear load (static and quasi static loading)	See Annex C3
Displacements	See Annex C4
Stiffness	No performance assessed
Characteristic resistance and displacements for seismic performance categories C1 and C2	No performance assessed

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Class A1
Resistance to fire	No performance assessed

3.3 Aspects of durability

Essential characteristic	Performance
Durability	See Annex B1

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with the European Assessment Document EAD 330232-02-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable European Assessment Document

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 27 May 2026 by Deutsches Institut für Bautechnik

Dipl.-Ing. Beatrix Wittstock
Head of Section

beglaubigt:
Baderschneider

Expandet Throughbolt EXG II




Table A1: Dimensions

Anchor size	Anchor length L			Wrench size
	Embedment depth $h_{ef,1}$	Embedment depth $h_{ef,2}$	Embedment depth $h_{ef,3}$	
M6	$t_{fix, h_{ef,1}} + 47,4$	$t_{fix, h_{ef,2}} + 57,4$	$t_{fix, h_{ef,3}} + 77,4$	10
M8	$t_{fix, h_{ef,1}} + 57,4$	$t_{fix, h_{ef,2}} + 66,4$	$t_{fix, h_{ef,3}} + 92,4$	13
M10	$t_{fix, h_{ef,1}} + 68,0$	$t_{fix, h_{ef,2}} + 74,0$	$t_{fix, h_{ef,3}} + 106,0$	17
M12	$t_{fix, h_{ef,1}} + 82,3$	$t_{fix, h_{ef,2}} + 97,3$	$t_{fix, h_{ef,3}} + 132,3$	19
M16	$t_{fix, h_{ef,1}} + 103,0$ $(t_{fix, h_{ef,1}} + 101,8)^{1)}$	$t_{fix, h_{ef,2}} + 121,0$ $(t_{fix, h_{ef,2}} + 117,8)^{1)}$	$t_{fix, h_{ef,3}} + 159,0$ $(t_{fix, h_{ef,3}} + 157,8)^{1)}$	24
M20	$t_{fix, h_{ef,1}} + 120,7$	$t_{fix, h_{ef,2}} + 142,7$	$t_{fix, h_{ef,3}} + 157,7$	30


¹⁾ Anchor version EXG II A2 / EXG II A4 / EXG II HCR

Marking: e.g.: $\diamond 15/21$

- $\diamond$ Identifying mark of manufacturing plant
- 15 maximum thickness of fixture for $h_{ef,2}$
- 21 maximum thickness of fixture for $h_{ef,1}$

additional marking:

- A2 stainless steel
- A4 stainless steel
- HCR high corrosion resistant steel



Marking of length	A	B	C	D	E	F	G	H	I	J	K	L	M
Length of anchor min $\geq$	38,1	50,8	63,5	76,2	88,9	101,6	114,3	127,0	139,7	152,4	165,1	177,8	190,5
Length of anchor max $<$	50,8	63,5	76,2	88,9	101,6	114,3	127,0	139,7	152,4	165,1	177,8	190,5	203,2

Marking of length	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
Length of anchor min $\geq$	203,2	215,9	228,6	241,3	254,0	279,4	304,8	330,2	355,6	381,0	406,4	431,8	457,2
Length of anchor max $<$	215,9	228,6	241,3	254,0	279,4	304,8	330,2	355,6	381,0	406,4	431,8	457,2	483,0

Dimensions in mm

Expandet Throughbolt EXG II

Product description
Marking and Dimensions

Annex A1

Table A2: Materials

Part	Designation	Material
Zinc plated steel		
Throughbolt EXG II	zinc plated	≥ 5 µm according to EN ISO 4042:1999
Throughbolt EXG II fvz	Hot-dip galvanized	≥ 50 µm (average coating thickness according to EN ISO 0684:2004+AC:2009 or EN ISO 1461:2009)
Throughbolt EXG II sh	Sherardized	≥ 45 µm according to EN ISO 17668:2016
1	Conical bolt	Cold formed or machined steel
2	Expansion sleeve	Stainless steel
3	Washer	Steel, zinc plated
4	Hexagon nut	Steel, zinc plated
Stainless steel		
Throughbolt EXG II A2 Stainless steel CRC II ¹⁾		
1	Conical bolt	Stainless steel
2	Expansion sleeve	Stainless steel
3	Washer	Stainless steel
4	Hexagon nut	Stainless steel
Throughbolt EXG II A4 Stainless steel CRC III ¹⁾		
1	Conical bolt	Stainless steel
2	Expansion sleeve	Stainless steel
3	Washer	Stainless steel
4	Hexagon nut	Stainless steel
Throughbolt EXG II HCR High corrosion resistant steel CRC V ¹⁾		
1	Conical bolt	High corrosion resistant steel
2	Expansion sleeve	Stainless steel
3	Washer	High corrosion resistant steel
4	Hexagon nut	High corrosion resistant steel

¹⁾ Corrosion resistance class according to EN 1993-1-4:2015, Annex A, Table A.3

Expandet Throughbolt EXG II

Product description
Materials

Annex A2

Specifications of intended use

Expandet Throughbolt EXG II		M6	M8	M10	M12	M16	M20
zinc plated steel	EXG II (zinc plated)	✓	✓	✓	✓	✓	✓
	EXG II fvz (hot-dip galvanized)	- ¹⁾	✓	✓	✓	✓	✓
	EXG II sh (sherardized)	✓	✓	✓	✓	✓	✓
stainless steel	EXG II A2	✓	✓	✓	✓	✓	✓
	EXG II A4	✓	✓	✓	✓	✓	✓
	EXG II HCR	✓	✓	✓	✓	✓	✓
all versions	static or quasi-static action	✓					
	uncracked concrete	✓					

1) No performance assessed

Base materials:

- Reinforced or unreinforced normal weight concrete without fibres according to EN 206:2013 + A1:2016
- Strength classes C20/25 to C50/60 according to EN 206:2013 + A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (all materials)
- For all other conditions:

Anchor version	Use according to EN 1993-1-4:2015 corresponding to the corrosion resistance class CRC according to Annex A, Table A2
EXG II A2	CRC II
EXG II A4	CRC III
EXG II HCR	CRC V

Design:

- Anchorage are designed under the responsibility of an engineer experienced in anchorages and concrete work.
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.).
- Anchorage are designed according to EN 1992-4:2018 or TR 055:2018.


Installation:

- Hole drilling by hammer drill bit or vacuum drill bit.
- Use of the fastener only as supplied by the manufacturer without exchanging the components of the fastener.
- The anchor can be set in pre- or through-setting installation.


Expandet Throughbolt EXG II	Annex B1
Intended use Specifications	

Installation parameters


Effective embedment depths $h_{ef,1}$



Effective embedment depths $h_{ef,2}$



Effective embedment depths $h_{ef,3}$



Expandet Throughbolt EXG II

Intended use
Installation parameters

Annex B2

Table B1: Installation parameters

Anchor size			M6	M8	M10	M12	M16	M20
Nominal drill hole diameter $d_0 =$ [mm]			6	8	10	12	16	20
Cutting diameter of drill bit $d_{cut} \leq$ [mm]			6,40	8,45	10,45	12,5	16,5	20,55
Installation torque	EXG II $T_{inst} =$ [Nm]	8	15	30	50	100	200	
	EXG II fvz $T_{inst} =$ [Nm]	2)	15	30	40	90	120	
	EXG II sh $T_{inst} =$ [Nm]	5	15	30	40	90	120	
	EXG II A2 EXG II A4 EXG II HCR $T_{inst} =$ [Nm]	6	15	25	50	100	160	
Diameter of clearance hole in the fixture $d_f \leq$ [mm]			7	9	12	14	18	22
Embedment depth $h_{ef,1}$								
Effective embedment depth $h_{ef,1} \geq$ [mm]			30	35	42	50	64	78
Depth of drill hole $h_{1,1} \geq$ [mm]			45	55	65	75	95	110
Embedment depth $h_{nom,1} \geq$ [mm]			39	47	56	67	84	99
Embedment depth $h_{ef,2}$								
Effective embedment depth $h_{ef,2} \geq$ [mm]			40	44	48	65	82 (80) ¹⁾	100
Depth of drill hole $h_{1,2} \geq$ [mm]			55	65	70	90	110	130
Embedment depth $h_{nom,2} \geq$ [mm]			49	56	62	82	102	121
Embedment depth $h_{ef,3}$								
Effective embedment depth $h_{ef,3} \geq$ [mm]			60	70	80	100	120	115
Depth of drill hole $h_{1,3} \geq$ [mm]			75	91	102	125	148	145
Embedment depth $h_{nom,3} \geq$ [mm]			69	82	94	117	140	136

¹⁾ Anchor version EXG II A2 / EXG II A4 / EXG II HCR

²⁾ No performance assessed

Expandet Throughbolt EXG II

Intended use
Installation parameters

Annex B3

Table B2: Minimum spacings and edge distances, zinc plated steel ¹⁾

Anchor size			M6	M8	M10	M12	M16	M20
Embedment depth $h_{ef,1}$								
Minimum member thickness	h_{min}	[mm]	80	80	100	100	130	160
Minimum spacing	s_{min}	[mm]	35	40	55	100	100	140
Minimum edge distance	c_{min}	[mm]	40	45	65	100	100	140
Embedment depth $h_{ef,2}$								
Minimum member thickness	h_{min}	[mm]	100	100	100	130	170	200
Minimum spacing	s_{min}	[mm]	35	40	55	75	90	105
Minimum edge distance	c_{min}	[mm]	40	45	65	90	105	125
Embedment depth $h_{ef,3}$								
Minimum member thickness	h_{min}	[mm]	120	126	132	165	208	215
Minimum spacing	s_{min}	[mm]	35	40	55	75	90	105
Minimum edge distance	c_{min}	[mm]	40	45	65	90	105	125

¹⁾ Anchor version EXG II fvz: M8-M20

Table B3: Minimum spacings and edge distances, stainless steel

Anchor size			M6	M8	M10	M12	M16	M20
Embedment depth $h_{ef,1}$								
Minimum member thickness	h_{min}	[mm]	80	80	100	100	130	160
Minimum spacing	s_{min}	[mm]	35	60	55	100	110	140
Minimum edge distance	c_{min}	[mm]	40	60	65	100	110	140
Embedment depth $h_{ef,2}$								
Minimum member thickness	h_{min}	[mm]	100	100	100	130	160	200
Minimum spacing	s_{min}	[mm]	35	35	45	60	80	100
	for $c \geq$	[mm]	40	65	70	100	120	150
Minimum edge distance	c_{min}	[mm]	35	45	55	70	80	100
	for $s \geq$	[mm]	60	110	80	100	140	180
Embedment depth $h_{ef,3}$								
Minimum member thickness	h_{min}	[mm]	120	126	132	165	200	215
Minimum spacing	s_{min}	[mm]	35	35	45	60	80	100
	for $c \geq$	[mm]	40	65	70	100	120	150
Minimum edge distance	c_{min}	[mm]	35	45	55	70	80	100
	for $s \geq$	[mm]	60	110	80	100	140	180





Intermediate values by linear interpolation.

Expandet Throughbolt EXG II

Intended use
Minimum spacings and edge distances

Annex B4

Installation instructions

1		Drill hole perpendicular to concrete surface. If using a vacuum drill bit, proceed with step 3.
2		Blow out dust. Alternatively, vacuum clean down to the bottom of the hole.
3		Drive in anchor, such that the selected embedment depth is met.
4		Apply installation torque T_{inst} as specified in Table B1.

Expandet Throughbolt EXG II

Intended use
Installation instructions

Annex B5

Table C1: Characteristic values for tension loads, zinc plated steel ¹⁾

Anchor size				M6	M8	M10	M12	M16	M20
Installation factor		γ_{inst}	[-]	1,0					
Steel failure									
Characteristic resistance		$N_{Rk,s}$	[kN]	8,7	15,3	26	35	65	107
Partial factor ⁴⁾		γ_{Ms}	[-]	1,5				1,6	
Pull-out									
Characteristic resistance in uncracked concrete C20/25	for $h_{ef,1}$	$N_{Rk,p}$	[kN]	6,5 ²⁾	10,2 ²⁾	13,4	17,4	25,2	33,9
	for $h_{ef,2}$	$N_{Rk,p}$	[kN]	10	13	16,4	25,8	36,5	49,2
	for $h_{ef,3}$	$N_{Rk,p}$	[kN]	10	13	16,4	26	40	55
Increasing factor $N_{Rk,p} = \psi_C \cdot N_{Rk,p} \text{ (C20/25)}$		ψ_C	[-]	$\left(\frac{f_{ck}}{20}\right)^{0,5}$				$\left(\frac{f_{ck}}{20}\right)^{0,33}$	$\left(\frac{f_{ck}}{20}\right)^{0,5}$
Splitting									
Characteristic resistance		$N^0_{Rk,sp}$	[kN]	min [$N_{Rk,p}$; $N^0_{Rk,c}$ ³⁾]					
Embedment depth $h_{ef,1}$									
Spacing		$s_{cr,sp}$	[mm]	180	210	230	240	320	400
Edge distance		$c_{cr,sp}$	[mm]	90	105	115	120	160	200
Embedment depth $h_{ef,2}$									
Spacing		$s_{cr,sp}$	[mm]	160	220	240	330	410	500
Edge distance		$c_{cr,sp}$	[mm]	80	110	120	165	205	250
Embedment depth $h_{ef,3}$									
Spacing		$s_{cr,sp}$	[mm]	160	220	240	330	410	520
Edge distance		$c_{cr,sp}$	[mm]	80	110	120	165	205	260
Concrete cone failure									
Effective embedment depth	for $h_{ef,1}$	[mm]	30 ²⁾	35 ²⁾	42	50	64	78	
	for $h_{ef,2}$	[mm]	40	44	48	65	82	100	
	for $h_{ef,3}$	[mm]	60	70	80	100	120	115	
Spacing		$s_{cr,N}$	[mm]	3 $h_{ef \text{ (1,2,3)}}$					
Edge distance		$c_{cr,N}$	[mm]	1,5 $h_{ef \text{ (1,2,3)}}$					
Factor	uncracked concrete	$k_{ucr,N}$	[-]	11,0					
	cracked concrete	$k_{cr,N}$	[-]	No performance assessed					

¹⁾ Anchor version EXG II fvz: M8-M20

²⁾ Restricted to the use of structural components with $h_{ef} < 40\text{mm}$ which are statically indeterminate and subject to internal exposure conditions only

³⁾ $N^0_{Rk,c}$ according to EN 1992-4:2018

⁴⁾ In absence of other national regulations

Expandet Throughbolt EXG II

Performance

Characteristic values for **tension loads, zinc plated steel**

Annex C1

Table C2: Characteristic values for tension loads, stainless steel

Anchor size				M6	M8	M10	M12	M16	M20
Installation factor		γ_{inst}	[-]	1,0					
Steel failure									
Characteristic resistance		$N_{Rk,s}$	[kN]	10	18	30	44	88	134
Partial factor ³⁾		γ_{Ms}	[-]	1,50					
Pull-out									
Characteristic resistance in uncracked concrete C20/25	for $h_{ef,1}$	$N_{Rk,p}$	[kN]	6,5 ¹⁾	9 ¹⁾	12	17,4	25,2	33,9
	for $h_{ef,2}$	$N_{Rk,p}$	[kN]	8	15	16,4	25	35,2	49,2
	for $h_{ef,3}$	$N_{Rk,p}$	[kN]	8	15	16,4	25	42	60
Increasing factor $N_{Rk,p} = \psi_C \cdot N_{Rk,p} \text{ (C20/25)}$		ψ_C	[-]	$\left(\frac{f_{ck}}{20}\right)^{0,5}$					
Splitting									
Characteristic resistance		$N^0_{Rk,sp}$	[kN]	$\min [N_{Rk,p} ; N^0_{Rk,c} \text{ }^2)]$					
Embedment depth $h_{ef,1}$									
Spacing		$s_{cr,sp}$	[mm]	180	210	230	300	320	400
Edge distance		$c_{cr,sp}$	[mm]	90	105	115	150	160	200
Embedment depth $h_{ef,2}$									
The higher one of the decisive resistances of Case 1 and Case 2 is applicable									
Case 1	Characteristic resistance	$N^0_{Rk,sp}$	[kN]	6	9	12	20	30	40
	Spacing	$s_{cr,sp}$	[mm]	3 h_{ef}					
	Edge distance	$c_{cr,sp}$	[mm]	1,5 h_{ef}					
	Increasing factor $N^0_{Rk,sp} = \psi_C \cdot N^0_{Rk,sp} \text{ (C20/25)}$	ψ_C	[-]	$\left(\frac{f_{ck}}{20}\right)^{0,5}$					
Case 2	Spacing	$s_{cr,sp}$	[mm]	160	220	240	340	410	560
	Edge distance	$c_{cr,sp}$	[mm]	80	110	120	170	205	280
Embedment depth $h_{ef,3}$									
Spacing		$s_{cr,sp}$	[mm]	160	220	240	340	410	620
Edge distance		$c_{cr,sp}$	[mm]	80	110	120	170	205	310
Concrete cone failure									
Effective embedment depth	for $h_{ef,1} \geq$	[mm]	30 ¹⁾	35 ¹⁾	42	50	64	78	
	for $h_{ef,2} \geq$	[mm]	40	44	48	65	80	100	
	for $h_{ef,3} \geq$	[mm]	60	70	80	100	120	115	
Spacing		$s_{cr,N}$	[mm]	3 h_{ef}					
Edge distance		$c_{cr,N}$	[mm]	1,5 h_{ef}					
Factor	uncracked concrete	$k_{ucr,N}$	[-]	11,0					
	cracked concrete	$k_{cr,N}$	[-]	No performance assessed					

¹⁾ Restricted to the use of structural components with $h_{ef} < 40\text{mm}$ which are statically indeterminate and subject to internal exposure conditions only

²⁾ $N^0_{Rk,c}$ according to EN 1992-4:2018

³⁾ In absence of other national regulations

Expandet Throughbolt EXG II

Performance
Characteristic values for **tension loads, stainless steel**

Annex C2

Table C3: Characteristic values for shear loads

Anchor size				M6	M8	M10	M12	M16	M20
Installation factor		γ_{inst}	[-]	1,0					
Steel failure without lever arm									
Characteristic resistance	zinc plated steel ¹⁾	$V^0_{\text{Rk,s}}$	[kN]	5	11	17	25	44	69
	stainless steel	$V^0_{\text{Rk,s}}$	[kN]	7	12	19	27	50	86
Ductility factor		k_7	[-]	1,0					
Steel failure with lever arm									
Characteristic bending resistance	zinc plated steel ¹⁾	$M^0_{\text{Rk,s}}$	[Nm]	9	23	45	78	186	363
	stainless steel	$M^0_{\text{Rk,s}}$	[Nm]	10	24	49	85	199	454
Partial factor ⁴⁾ for $V^0_{\text{Rk,s}}$ and $M^0_{\text{Rk,s}}$	zinc plated steel ¹⁾	γ_{Ms}	[-]	1,25				1,33	
	stainless steel	γ_{Ms}	[-]	1,25					1,4
Concrete pry-out failure									
Factor for h_{ef}	zinc plated steel ¹⁾	k_8	[-]	1,0	2,3	2,5	2,9	2,8	3,1
	stainless steel	k_8	[-]	1,0	2,3	2,8	2,8	3,0	3,3
Concrete edge failure									
Effective length of anchor in shear loading	for $h_{\text{ef},1}$	l_f	[mm]	30 ²⁾	35 ²⁾	42	50	64	78
	for $h_{\text{ef},2}$	l_f	[mm]	40	44	48	65	82 (80) ³⁾	100
	for $h_{\text{ef},3}$	l_f	[mm]	60	70	80	100	120	115
Outside diameter of anchor		d_{nom}	[mm]	6	8	10	12	16	20

¹⁾ Anchor version EXG II fvz: M8-M20

²⁾ Restricted to the use of structural components which are statically indeterminate and subject to internal exposure conditions only

³⁾ Anchor version stainless steel

⁴⁾ In absence of other national regulations

Expandet Throughbolt EXG II

Performance
Characteristic values for **shear loads**

Annex C3

Table C4: Displacements under tension load

Anchor size			M6	M8	M10	M12	M16	M20
Embedment depth $h_{ef,1}$								
zinc plated steel ¹⁾								
Tension load	N	[kN]	2,9	5,0	6,5	8,5	12,3	16,6
Displacement	δ_{N0}	[mm]	0,3	0,4				
	$\delta_{N\infty}$	[mm]	0,6	1,8				
stainless steel								
Tension load	N	[kN]	2,9	4,3	5,7	8,5	12,3	16,6
Displacement	δ_{N0}	[mm]	0,4	0,7	0,4	0,4	0,6	1,5
	$\delta_{N\infty}$	[mm]	1,3					2,9
Embedment depth $h_{ef,2}$ and $h_{ef,3}$								
zinc plated steel ¹⁾								
Tension load	N	[kN]	4,3	5,8	7,6	11,9	16,7	23,8
Displacement	δ_{N0}	[mm]	0,4	0,5				
	$\delta_{N\infty}$	[mm]	0,7	2,3				
stainless steel								
Tension load	N	[kN]	3,6	5,7	7,6	11,9	17,2	24,0
Displacement	δ_{N0}	[mm]	0,7	0,9	0,5	0,6	0,9	2,1
	$\delta_{N\infty}$	[mm]	1,8					4,2

¹⁾ Anchor version EXG II fvz: M8-M20

Table C5: Displacements under shear loads

Anchor size			M6	M8	M10	M12	M16	M20
zinc plated steel ¹⁾								
Shear load	V	[kN]	2,9	6,3	9,7	14,3	23,6	37,0
Displacement	δ_{V0}	[mm]	1,2	1,5	1,6	2,6	3,1	4,4
	$\delta_{V\infty}$	[mm]	2,4	2,2	2,4	3,9	4,6	6,6
stainless steel								
Shear load	V	[kN]	4,0	6,9	10,9	15,4	28,6	43,7
Displacement	δ_{V0}	[mm]	1,1	2,0	1,2	2,0	2,2	2,1
	$\delta_{V\infty}$	[mm]	1,7	3,0	1,8	3,0	3,3	3,2

¹⁾ Anchor version EXG II fvz: M8-M20

Expandet Throughbolt EXG II

Performance
Displacements

Annex C4